# 8736SEO2V02H30S

NEMA starter, Type S, reversing, horizontal, Size 3, 90A, 50HP at 575VAC, up to 100kA SCCR, 3 phase, 3 pole, Motor Logic SSOLR, 120VAC coil, open



#### Main

Product Type	Starter
Product Range	S
Starter Type	Reversing

Complementary

NEMA Size	3	
Rated Current	90 A	
Number of Poles	3P	
Mounting Orientation	Horizontal	
Wiring Mode	3 wires	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Solid state Motor Logic class 10/20	
Horsepower Rating	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC	
SCCR	Circuit-breaker 150 A maximum: 100 kA at 480 V AC Fuse J 200 A maximum: 100 kA at 600 V AC Fuse T 200 A maximum: 100 kA at 600 V AC Fuse RK1 200 A maximum: 100 kA at 600 V AC Fuse RK5 200 A maximum: 100 kA at 600 V AC	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	11.72 in (297.69 mm)	
Width	12.72 in (323.09 mm)	
Depth	7.00 in (177.80 mm)	

#### Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed[RETURN]CSA

## Ordering and shipping details

Category	21273-8702,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901956020
Returnability	No
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.50 in (24.13 cm)
Package 1 Width	13.50 in (34.29 cm)
Package 1 Length	18.00 in (45.72 cm)
Package 1 Weight	35.83 lb(US) (16.252 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	<sup>™</sup> China RoHS Declaration

#### Contractual warranty

Warranty	18 months
Transity	To months