

# Silver Brazed Barrel

## 8 WIRE RANGE

.050 Stock

| Stud Size | Part Number     |
|-----------|-----------------|
| 8-10      | R2E10<br>R2E10S |
| 12-1/4    | R2E14S          |
| 1/4-5/16  | R2E56           |
| 5/16-3/8  | R2E38           |
| 7/16-1/2  | R2E50           |
|           | Parallel P7E    |
|           | Butt B7E        |

**Terminals are NOT Actual Size**

## 6 WIRE RANGE

.057 Stock

| Stud Size | Part Number  |
|-----------|--------------|
| 8-10      | R2F10        |
| 12-1/4    | R2F14S       |
| 1/4-5/16  | R2F56        |
| 5/16-3/8  | R2F38        |
| 7/16-1/2  | R2F50        |
|           | Parallel P7F |
|           | Butt B7F     |


600 Volt Rated

**Copper Stranded Wire Only**



| DIMENSIONAL CHART |        |        |
|-------------------|--------|--------|
| Part Number       | W      | L      |
| B7E               |        | 0.832" |
| P7E               |        | 0.378" |
| R2E10             | 0.470" | 0.962" |
| R2E10S            | 0.377" | 0.925" |
| R2E10SS           | 0.375" | 0.922" |
| R2E14S            | 0.469" | 0.951" |
| R2E38             | 0.590" | 1.078" |
| R2E50             | 0.859" | 1.336" |
| R2E56             | 0.590" | 1.088" |
| R2E8SS            | 0.377" | 0.936" |

600 Volt Rated



| DIMENSIONAL CHART |        |        |
|-------------------|--------|--------|
| Part Number       | W      | L      |
| B7F               |        | 1.022" |
| P7F               |        | 0.477" |
| R2F10             | 0.626" | 1.233" |
| R2F10S            | 0.645" | 1.268" |
| R2F14             | 0.635" | 1.249" |
| R2F14S            | 0.451" | 1.163" |
| R2F38             | 0.634" | 1.246" |
| R2F50             | 0.827" | 1.447" |
| R2F56             | 0.645" | 1.268" |



Approved installation tool: RHT/192850004  
 Economy installation tools: LUG-12-4, LUG-8-4  
 See pages E-2 to E-5 for installation tools.

**B**