



Main

Range of Product	PowerPact
Device Application	Tripping device
Accessory / separate part category	Trip unit accessory
Circuit breaker name	FAL/FCL/FHL
Circuit breaker type	FA/FH/FC

Complementary

Poles description	2P or 3P
Mounting Mode	Internal mounting
Location of connection	Inside
Rated voltage	120...240 V AC
Protection Type	Shunt trip protection
Type of Installation	Field installable
Tightening torque	6.20...8.85 lbf.in (0.7...1 N.m)

Environment

Product Certifications	UL[RETURN]CSA
------------------------	---------------

Ordering and shipping details

Category	00985-FIA FOR ALL BREAKERS
Discount Schedule	DE2
GTIN	785901005766
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.82 in (9.7 cm)
Package 1 Width	4.29 in (10.9 cm)
Package 1 Length	8.90 in (22.6 cm)
Package 1 Weight	10.24 oz (290.3 g)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------