

Product Datasheet

Characteristic

8501C016V24

Power Relay - 240VAC Coil - DPDT -
2NO-2NC - 1.5 HP - 30A Resistive at
300V



Main

range of product	Power Relay 8501C
product or component type	Power relay
device short name	Type C
Line Rated Current	30 A
device application	Suited for controlling small single phase motors and other light loads
switch function	DPDT
contacts type and composition	2 NO/2 NC
[Uc] control circuit voltage	240 V AC 50/60 Hz
rated power in hp	1.5 hp
maximum switching voltage	600 V AC

Complementary

catalog class	8501
Phase	1 phase
connections - terminals	Screw clamp terminal
AWG gauge	AWG 10 copper
tightening torque	11...15 lbf.in
hold-in power consumption in VA	10 VA
mounting support	Panel mounting

Environment

ambient air temperature for operation	-22...122 °F
product certifications	CE UL listed file E78351 CCN NLDX
height	3.12 in
width	2.5 in
depth	2.31 in

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1014 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations