



Main

| | |
|---------------------------|--------------------------------|
| Product or Component Type | Industrial Control Transformer |
| Type | TF |

Complementary

| | |
|--------------------------------|--|
| Number of Phases | 1 phase |
| Power Rating | 50 VA UL[RETURN]50 VA CSA[RETURN]50 VA NOM[RETURN]50 VA CE |
| Primary to Secondary Voltage | 208 V 120 V |
| Fuse type | 0.41 x 1.50 in CC top |
| Temperature rise | 55 °C |
| Electrical Connection | Screw clamp terminals |
| Height | 4 in (101.60 mm) |
| Width | 3 in (76.20 mm) |
| Depth | 3.09 in (78.49 mm) |
| Material | Copper: winding |
| Fingersafe Cover Compatibility | FSC1 |

Environment

| | |
|------------------------|--|
| Product Certifications | UL listed file E61239[RETURN]CSA file LR37055 guide 184-N-90 |
| Enclosure Type | Not rated (open device) |
| Insulation temperature | 221 °F (105 °C) |

Ordering and shipping details

| | |
|-------------------|--------------------------------|
| Category | 16202-9070 TF (NOT T) 50-200VA |
| Discount Schedule | CP8 |
| GTIN | 785901905790 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.80 in (17.272 cm) |
| Package 1 Width | 7.10 in (18.034 cm) |
| Package 1 Length | 8.00 in (20.32 cm) |
| Package 1 Weight | 3.19 lb(US) (1.447 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|