

Direct Burial/ Submersible Splice Kits With Heat Shrink

SK SERIES



FEATURES

1. COPPER BUTT SPLICE KITS

Mechanical copper butt splice and a heavy wall heat shrink tubing to create a fully insulated splice for copper conductors only.

3. UF CABLE SPLICE KIT

For simplified splicing of UF cable designed with heavy wall heat shrink with sealant. This kit will accommodate 14/3 through 8/3 with ground UF cable and create a direct burial splice. Contains one four-position connector.

2. DUAL RATED BUTT SPLICE KITS

Mechanical dual rated splice and matched heavy wall heat shrink tubing to create an insulated splice for copper and/or aluminum cables.

4. UF STRETCHER KIT

Eliminates the need for using two connectors and a short piece of cable when repairing damaged UF cable. Includes one 11.5" connector that will accommodate 14/3 without GRD minimum and 8/3 with GRD maximum. 600 Volt, 105°C. Utilizes heavy wall shrink with sealant for a quick and reliable repair.

RATINGS



TEMPERATURE RATING:

105 °C.
600V Max.



All dimensional data is listed in inches.

CAT. NO.	FIG. NO.	RANGE	STD. CTN. QTY.
SKCB-8	1	#14 to #8 AWG	24
SKCB-2	1	#8 to #2 AWG	24
SKAB-2	2	#8 to #2 AWG	24
SKAB-0	2	#6 to 1/0 AWG	24
SKAB-250	2	1/0 AWG to 250 MCM	12
SKDB	3	14/3 to 8/3	24
SKUF	4	14/3 to 8/3	12