## 760238142 | USL600-SHLD, BLU



Uniprise SLX Series Modular Jack, category 6, shielded , 4 Pair, without dust cover, blue

- Fits all existing SL panels and faceplates
- Universal latch for SL series
- 9 Different color options Replaceable color caps
- Terminated with SL Series termination tool
- Wire holder cut off during termination
- Universal wiring label
- Easy re-termination

## **Product Classification**

Regional AvailabilityNorth AmericaPortfolioUniprise®Product TypeModular jackProduct SeriesSLX Series

## General Specifications

ANSI/TIA Category 6

Cable TypeShieldedColorBlue

Conductor Type Solid | Stranded

Integrated Dust Cover Type None

Mounting SL Series faceplates and panels

Outlet Type Standard

**Termination Tool** SL Termination tool

Termination Type IDC

Transmission Standards ANSI/TIA-568-C.2 | ISO/IEC 11801 Class E

**Wiring** T568A | T568B

Dimensions

**Panel Cutout, recommended** 14.78 x 20.07 mm (0.58 x 0.79 in)

 Panel Thickness, recommended
 1.6 mm | 0.063 in

 Height
 16.13 mm | 0.635 in

 Width
 14.48 mm | 0.57 in

Page 1 of 2



## 760238142 | USL600-SHLD, BLU

**Depth** 36.8 mm | 1.449 in

**Compatible Cable Diameter, maximum** 8.5 mm | 0.335 in

Compatible Insulated Conductor Diameter, maximum 1.6 mm | 0.063 in

Contact Plating Thickness 1.27 µm

Compatible Conductor Gauge, solid 26-22 AWG

Compatible Conductor Gauge, stranded 26-24 AWG

**Electrical Specifications** 

**Remote Powering** Fully supports the safe delivery of power over LAN cabling described

by IEEE 802.3bt (Type 4) and complies with the unmating under electrical load requirements prescribed by IEC 60512-99-002

Material Specifications

Contact Base Material Beryllium copper

Contact Plating Material Gold

Material Type Polycarbonate | Zamak

**Environmental Specifications** 

**Operating Temperature**  $-10 \,^{\circ}\text{C}$  to  $+60 \,^{\circ}\text{C}$  (+14  $^{\circ}\text{F}$  to +140  $^{\circ}\text{F}$ )

Flammability Rating UL 94 V-0

Packaging and Weights

Packaging quantity 24

Packaging Type Bag | Box

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



