760118323 | M2400-1U-GS



Product Classification

Storage Temperature

Relative Humidity

M2400 1U Modular Panel, 24 port (MGS600 / MGS400)

PIUUULI CIASSIIILALIUII	
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Portfolio	CommScope®
Product Type	RJ45 patch panel
Product Brand	GigaSPEED X10D®
General Specifications	
ANSI/TIA Category	6 6A
Cable Type	Unshielded
Color	Black
Intelligence Type	Passive
Rack Type	EIA 19 in
Rack Units	1
Total Ports, quantity	24
Dimensions	
Height	43.69 mm 1.72 in
Width	482.6 mm 19 in
Depth	53.59 mm 2.11 in
Compatible Diameter Over Dielectric, maximum	1.168 mm 0.046 in
Compatible Diameter Over Dielectric, minimum	0.762 mm 0.03 in
Material Specifications	
Material Type	High-impact, flame retardant, thermoplastic Powder-coated steel
Environmental Specifications	
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)

-40 °C to +70 °C (-40 °F to +158 °F)

Up to 95%, non-condensing

Page 1 of 2

©2022 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: February 3, 2022



760118323 | M2400-1U-GS

Flammability Rating

UL 94 V-0

Safety Standard

UL | cUL

Packaging and Weights

Packaging quantity

1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant



Page 2 of 2

©2022 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: February 3, 2022

