



## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJD37H29 ZCKJ11 ZCKJ5H7 ZCKJD39H29 ZCKJ2H7 ZCKJ5H29 ZCKJ1H7 ZCKJD39H7 ZCKJ11H29 ZCKJD35H7 ZCKJD31H7 ZCKJ7H29 ZCKJ8H29 ZCKJD31H29 ZCKJ2 ZCKJ1 ZCKJD35 ZCKJ5 ZCKJ6 ZCKJ21H7 ZCKJ41 ZCKJD37 ZCKJ9 ZCKJ11H7 ZCKJ7H7 ZCKJ21H29 ZCKJ41H29 ZCKJ4 ZCKJ2H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJD37H7  
 ZCKJ4H29  
 ZCKJD35H29  
 ZCKJD39  
 ZCKJ9H29  
 ZCKJ6H7  
 ZCKJ21  
 ZCKJ9H7  
 ZCKJD31  
 ZCKJ8H7  
 ZCKJ6H29  
 ZCKJ41H7  
 ZCKJ7  
 ZCKJ1H29  
 ZCKJ8  
 ZCKJ4H7

Movement of operating head	Linear
Type of operator	Roller lever plunger spring return thermoplastic
Type of approach	Lateral approach, 1 direction

### Complementary

Switch actuation	By 30° cam
Positive opening	With
Net weight	0.41 lb(US) (0.185 kg)
Head material	Metal

### Environment

Ambient air temperature for operation	50...248 °F (10...120 °C)
Ambient air temperature for storage	50...248 °F (10...120 °C)
Environmental characteristic	High temperature

### Packing Units

Package 1 Weight	0.41 lb(US) (0.185 kg)
Package 1 Height	0.060 dm
Package 1 width	0.044 dm
Package 1 Length	0.055 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------