

CABLE TIES

UV & Weather Resistant (Black) Cable Ties



FEATURES

- Made from weather resistant Nylon 66 for applications exposed to outside elements.
- UV resistant.
- Black only.

RATINGS



TEMPERATURE RATINGS:

Min., -40°F to Max., 185°F (-40°C to 85°C)

IDEAL STORAGE:

23°C, Humidity 50%, Avoid storing cable ties next to warm objects

TYPE 21 AH-2:

"Suitable for use in air-handling spaces (Plenums)"

MAX. WIRE/ CABLE SIZE (L)	CAT. NO.
4"	4180
	4180X
	4500
5"	4500X
	5180
	5180X
	5400
6"	5400X
	6500
7"	7500
	7500X
	8180
8"	8180X
	8400
	8400X
	8500
	8500X
	8750
	81200
11"	11400
	11500
	11500X
	11750
	111200
14"	14500
	14500X
	14750
15"	141200
	152500
18"	18500
	181750
	182500
22"	222500
24"	241750
28"	282500
30"	301750
34'	342500
36"	361750
40"	402500
48"	481750
60"	601750



MAX BUNDLE DIAMETER	TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
0.800	18 Lbs	4.000	0.095	100	5,000
0.800	18 Lbs	4.000	0.095	1000	5,000
1.430	50 Lbs	6.000	0.095	100	5,000
1.375	50 Lbs	5.500	0.100	1000	5,000
1.300	18 Lbs	5.500	0.140	100	3,000
1.300	18 Lbs	5.000	0.140	1000	3,000
1.320	40 Lbs	6.250	0.181	100	3,000
1.320	40 Lbs	6.300	0.181	1000	3,000
1.810	40 Lbs	7.500	0.189	100	3,000
2.060	50 Lbs	8.000	0.095	100	3,000
2.060	50 Lbs	8.000	0.095	1000	3,000
2.060	18 Lbs	8.000	0.140	100	3,000
2.060	18 Lbs	8.000	0.140	1000	3,000
1.940	40 Lbs	8.000	0.189	100	3,000
1.940	40 Lbs	8.000	0.189	1000	3,000
2.000	50 Lbs	8.000	0.300	100	2,000
2.000	50 Lbs	8.000	0.300	1000	2,000
2.000	75 Lbs	8.000	0.300	100	2,000
3.300	120 Lbs	11.500	0.140	100	2,000
2.940	40 Lbs	11.100	0.189	100	2,000
3.125	50 Lbs	11.500	0.187	100	2,000
3.125	50 Lbs	11.500	0.187	1000	2,000
3.000	75 Lbs	11.500	0.189	100	2,000
3.000	120 Lbs	11.500	0.300	100	2,000
4.070	50 Lbs	14.100	0.189	100	3,000
4.070	50 Lbs	14.100	0.189	1000	3,000
4.070	75 Lbs	14.100	0.189	100	3,000
4.070	120 Lbs	14.250	0.300	100	2,000
4.375	250 Lbs	15.000	0.500	50	500
5.070	50 Lbs	18.000	0.189	100	2,000
5.250	175 Lbs	17.750	0.315	50	500
5.500	250 Lbs	18.870	0.500	50	500
6.875	250 Lbs.	22.87	0.500	50	500
7.140	175 Lbs	24.000	0.345	50	500
8.875	250 Lbs.	28.75	0.500	50	500
9.250	175 Lbs	30.000	0.354	50	500
10.5	250 Lbs.	34.68	0.500	50	500
11.000	175 Lbs	36.000	0.350	50	500
12.5	250 Lbs.	40.5	0.500	50	500
15.000	175 Lbs	48.000	0.354	50	500
18.250	175 Lbs	59.000	0.354	50	500