QOB115EPD

Mini circuit breaker, QO, 15A, 1 pole, 120VAC, 10kA, 30mA grd fault B, bolt on mount





Main	
Product	Miniature circuit-breaker
Range	QO
Current Rating	15 A
Voltage Rating	120 V AC
Mounting Type	Bolt-on
Number of Poles	1P
Circuit Breaker Type	Ground fault protecting class B 30 mA
Ratings	Not rated
Electrical Connection	Pressure plate

Com	-		1
L.Am	വല	me	ntarv
OULL	$\mathbf{p}_{\mathbf{i}}\mathbf{c}$		ntany

o o p · o · · o · · o · · o · · o · · o · · o · · o · · o · · o · · o · · o · · o · o · · o · o · o · o · · o ·		
Interrupt Rating	10 kA 120 V AC 50/60 Hz	
Number of Panel Spaces	1	
Wire Size	AWG 14AWG 8 copper AWG 12AWG 8 aluminium	
Tightening Torque	35.40 Lbf.ln (4 N.m) 40.71 lbf.in (4.6 N.m) 0.010.03 in² (420 mm²) (AWG 12AWG 4)	
Height	4.13 in (105 mm)	
Width	0.75 in (19 mm)	
Depth	2.91 in (74 mm)	
Net Weight	0.52 lb(US) (0.236 kg)	

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

0 11 0	
Category	00910-QO-EPD,QOB-EPD BREAKERS
Discount Schedule	DE2A
GTIN	785901763673
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.30 in (3.302 cm)	
Package 1 Width	5.50 in (13.97 cm)	
Package 1 Length	3.90 in (9.906 cm)	
Package 1 Weight	8.32 oz (235.868 g)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	

Contractual warranty

Warranty 18 months	
--------------------	--