Product data sheet Characteristics

P3U3

APC Essential SurgeArrest, 3 Outlets, 3 USB Charging Ports, 120V







Overview

Lead time Usually in Stock

General

| Provided equipment | User Manual |
|--------------------|-------------|
|--------------------|-------------|

Physical

| 6 ft (1.83 m) | |
|-----------------------|---|
| White | |
| 5.20 in (13.22 cm) | |
| 1.42 in (3.6 cm) | |
| 1.08 lb(US) (0.49 kg) | |
| 5.20 in (13.22 cm) | |
| | White 5.20 in (13.22 cm) 1.42 in (3.6 cm) 1.08 lb(US) (0.49 kg) |

Input

| Input power | 1440 W |
|----------------------------|------------|
| Input Frequency | 60 Hz |
| Plug standard | NEMA 5-15P |
| Switching current capacity | 12 A |
| Nominal Input Voltage | 120 V |

Output

| Number of power socket outlets | 3 |
|--------------------------------|------------|
| Outlet standard | NEMA 5-15R |

Conformance

| Product Certifications | CUL Listed |
|-----------------------------|-------------------|
| Standards | UL 60950-1 |
| Equipment protection policy | Lifetime: \$50000 |

Environmental

| Ambient Air Temperature for Operation | 32104 °F (040 °C) |
|---------------------------------------|----------------------------|
| Relative Humidity | 095 % |
| Operating altitude | 010000 ft |
| Ambient Air Temperature for Storage | 5113 °F (-1545 °C) |
| Storage Relative Humidity | 095 % |
| Storage altitude | 050000 ft (0.0015240.00 m) |

Surge Protection and Filtering

| NM Surge Response Time (ns) | 1 ns common mode |
|-----------------------------|------------------|
| Common mode rejection | 40 dB |
| Surge energy rating | 1080 J |

Ordering and shipping details

| GTIN | 00731304315193 |
|---------------------|-----------------------|
| Package weight(Lbs) | 1.17 lb(US) (0.53 kg) |

Packing Units

| r doming office | |
|------------------------------|------------------------|
| Package 1 Height | 2.95 in (7.5 cm) |
| Package 1 width | 5.39 in (13.7 cm) |
| Package 1 Length | 6.10 in (15.5 cm) |
| SCC14 | 10731304315190 |
| Number of Units in Package 2 | 10 |
| Package 2 Weight | 13.64 lb(US) (6.19 kg) |
| Package 2 Height | 6.87 in (174.50 mm) |
| Package 2 width | 11.25 in (285.75 mm) |
| Package 2 Length | 15.75 in (400.05 mm) |
| Number of Units in Package 3 | 80 |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | ☑ REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant E EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | ₽¥Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|------------------|
| Warranty | Limited Lifetime |