



Catalog N°:
K2A44U

BURNDY Catalog Number	K2A44U
UPC Number	781810600306
Description	TWO:500-1000 DUAL RATED
Status	Active
Web Use	
BURNDY Product Line	
Dimensional	
Width (in)	3.52
Length (in)	3.50
Bolt Hole Size (in)	0.63
Thickness	0.50
D - in	1.66
Pad Width (in)	3.52
N (in)	0.88
General	
Number of Conductors	2
Number of Holes	1





Product Description	Aluminum Universal Terminal, 2 Conductor, 1 Hole, 500-1000 kcmil, 5/8" Stud, 2 Screws, Al/Cu Rated, Tin Plated
Conductor(s)	
Aluminum Size (Range)	500 kcmil-1000 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	500 kcmil-1000 kcmil
Physical	
Installation Torque	500
Type of Plating	Tin
Connector Type	Terminal
Bolt Hole Size	5/8
Plated (Yes or No)	N
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Non-Compliant





UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

