Q432300

Circuit breaker, Q4, 300A, 3 pole, 240VAC, 25kA, I-Line, thermal magnetic





Main	
Product or Component Type	Circuit breaker
Range	PowerPact
Trip Unit Technology	Thermal-magnetic

Com	nler	neni	tarv
COIII	pici		ıcı y

Line Rated Current	300 A
Number of Poles	3P
Breaking capacity code	Q4
Mounting Mode	I-Line
Magnetic Hold Current	1500 A
Magnetic Tripping Current	3000 A
Electrical connection	Lugs, load I-Line connection, line
Terminal identifier	AL400LA
Tightening torque	115.06 Lbf.In (13 N.m) 0.070.47 in² (42304 mm²) (AWG 1600 kcmil) 115.06 lbf.in (13 N.m) 0.070.20 in² (42127 mm²) (AWG 1250 kcmil)
Height	11 in (279.40 mm)
Width	6 in (152.40 mm)
Depth	5.84 in (148.34 mm)

Environment

LITTITOTITICITE		
Certifications	CSA[RETURN]UL Listed	

Ordering and shipping details

Category	01038-Q4 BREAKER & SWITCH
Discount Schedule	DE2
GTIN	785901649311
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	9.00 in (22.86 cm)	
Package 1 Width	11.50 in (29.21 cm)	
Package 1 Length	17.40 in (44.196 cm)	
Package 1 Weight	17.97 lb(US) (8.15 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	
Contractual warranty		
Warranty	18 months	