

Product Datasheet

Characteristic

ZBVB45

red light block for head Ø22 integral LED
24V spring clamp terminals



Main

range of product	Harmony XB4 Harmony XB5
product or component type	Light block
device short name	ZBV
sale per indivisible quantity	4
connections - terminals	Spring clamp terminals
signalling type	Steady
light source	Protected LED
bulb base	Integral LED
light block supply	Direct
light source colour	Red
[Us] rated supply voltage	24 V AC/DC, 50/60 Hz

Complementary

product weight	0.04 lb(US) (0.016 kg)
supply voltage limits	19.2...30 V DC 21.6...26.4 V AC
current consumption	18 mA
service life	100000 h at rated voltage and 25 °C
surge withstand	1 kV conforming to IEC 61000-4-5
mounting of block	Front mounting
electrical composition code	M1 M2 M3 M4 M5 M6 M10 MF1 P1 P2 PF1
compatibility code	ZBV

Environment

protective treatment	TH
----------------------	----

ambient air temperature for storage	-40...158 °F (-40...70 °C)
ambient air temperature for operation	-40...158 °F (-40...70 °C)
IP degree of protection	IP20 conforming to IEC 60529
standards	EN/IEC 60947-5-5 CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60947-1 UL 508 JIS C 4520 EN/IEC 60947-5-4
resistance to fast transients	2 kV conforming to IEC 61000-4-4
resistance to electromagnetic fields	9.14 V/yd (10 V/m) conforming to IEC 61000-4-3
resistance to electrostatic discharge	6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2
electromagnetic emission	Class B conforming to IEC 55011