

RCD Safety Switches

The RCD line of Safety Switches is a cost-effective commercial disconnect – perfect for outdoor HVAC, Air Handling and Air Compressor applications.

Feature include:

- 30A (20HP) and 60A (30HP) 600V ratings
- Suitable for use as a motor disconnect
- Outdoor Type 3R Enclosure
- Front accessible terminals
- Foolproof mechanism installation (reject feature)
- Compact design less that 9" tall
- 4 sets of 1/2 3/4" Knockouts
- Flush backwall
- Multi-port ground lug
- Easy to remove cover for fast installation

EEMAC 3R Non-Fused Weatherproof Switches (600V Maximum)

Poles	Amp	Cat. Number	Max. HP Rating			
	Rating		120 VAC	240 VAC	480 VAC	600 VAC
2	30	RCD5326	2	5	10	15
3	30	RCD5336	3	7.5	15	20
2	60	RCD5626	-	10	15	20
3	60	RCD5636	-	10	25	30

Height
8 3/4" (222mm)
Width
4 1/2" (114mm)
Depth
3 1/4" (83mm)
3 1/4" (83mm) Height (with handle)

For more information, contact your local Schneider Electric distributor, Schneider Electric sales representative or contact our customer information centre at 1-800-565-6699.

www.schneider-electric.ca



by Schneider Electric