Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.579 Date : Mar 14, 2018

RITTAL

ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure – WM 8017.579 - WM363012NC

: 14.03.2018 build on www.rittal.com/ca-en



Product description	
Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert
Product features	
Dimensions:	Height: 900 mm (35 ″) Width: 760 mm (30 ″) Depth: 300 mm (12 ″)
Material thickness::	Housing: 2 mm (0.08 ″) Door: 2 mm (0.08 ″) Mounting plate: 2.5 mm (0.1 ″)
Mounting plate:	Height: 870 mm (34 ″) Width: 704 mm (28 ″)

1

1 pc(s).
55 kg (121.3 lb.)
83156
UL