

ELECTRICAL

Bolt Cutters



Bolt Cutters

- Hardened alloy steel jaws are designed and manufactured to assure the longest possible blade life.
- One-step internal cam mechanism provides the quickest and simplest way to keep the cutting blades precisely aligned.
- Handles and grips designed to allow greater mechanical advantage for crisp, controlled cutting.

| Catalog No. | Model No. | Description | Capacity/Metals | | | | | | Weight | |
|-------------|-----------|-------------|-------------------------------|------|------------------------------|------|------------------------------|------|--------------------------------|------|
| | | | Soft (15RC) ¹ | | Medium (31RC) ² | | Hard (42RC) ³ | | lb. | kg |
| | | | in. | mm | in. | mm | in. | mm | | |
| 14213 | S14 | Center Cut | ⁵ / ₁₆ | 7.9 | ¹ / ₄ | 6.4 | ³ / ₁₆ | 4.8 | 1 ¹ / ₄ | 1.00 |
| 14218 | S18 | Center Cut | ³ / ₈ | 9.5 | ⁵ / ₁₆ | 7.9 | ¹ / ₄ | 6.4 | 3 ³ / ₈ | 1.50 |
| 14223 | S24 | Center Cut | ⁷ / ₁₆ | 11.0 | ³ / ₈ | 9.5 | ⁵ / ₁₆ | 7.9 | 5 ⁷ / ₈ | 2.70 |
| 14228 | S30 | Center Cut | ¹ / ₂ | 12.7 | ⁷ / ₁₆ | 11.0 | ³ / ₈ | 9.5 | 8 ⁷ / ₈ | 4.00 |
| 14233 | S36 | Center Cut | ⁹ / ₁₆ | 14.3 | ¹ / ₂ | 12.7 | ⁷ / ₁₆ | 11.0 | 13 ¹ / ₂ | 6.10 |
| 14238 | S42 | Center Cut | ¹¹ / ₁₆ | 17.5 | ⁹ / ₁₆ | 14.3 | ¹ / ₂ | 12.7 | 18 ¹ / ₄ | 8.30 |

Replacement Heads

| Catalog No. | Description | Weight | |
|-------------|-------------------|--------------------------------|-----|
| | | lb. | kg |
| 18363 | S14 Head Assembly | ⁷ / ₈ | 1.0 |
| 18368 | S18 Head Assembly | 1 ¹ / ₄ | 1.5 |
| 18373 | S24 Head Assembly | 2 ¹ / ₄ | 2.7 |
| 18378 | S30 Head Assembly | 8 ⁷ / ₈ | 4.0 |
| 18383 | S36 Head Assembly | 13 ¹ / ₂ | 6.1 |
| 18388 | S42 Head Assembly | 18 ¹ / ₄ | 8.3 |

Cable Cutters



No. 1380 Cable Cutter

- The Model 1380 Cable Cutter is designed to shear-cut insulated aluminum and copper cable through 1³/₈" diameter and 750 MCM*. Drop-forged, heat-treated, alloy steel jaws shear cable with minimum distortion of internal wires. Fitted with fiberglass-insulated handles and rubber grips.

*Not intended for cutting steel or ACSR cable.

| Catalog No. | Model No. | Description | Weight | |
|-------------|-----------|--|-------------------------------|-----|
| | | | lb. | kg |
| 83350 | 1380 | Aluminum and Copper Cable through 1 ³ / ₈ Diameter and 750 MCM | 4 ¹ / ₂ | 2.0 |