

DEK 5/3,5 MC FSZ 1-10

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.



General ordering data

| | |
|------------|--|
| Version | Dekafix, Terminal marker, 5 x 3.5 mm, Pitch in mm (P): 3.50 Weidmueller, white |
| Order No. | 1762320001 |
| Type | DEK 5/3,5 MC FSZ 1-10 |
| GTIN (EAN) | 4032248043552 |
| Qty. | 500 pc(s). |

DEK 5/3,5 MC FSZ 1-10

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Height | 5 mm | Height (inches) | 0.197 inch |
| Width | 3.5 mm | Width (inches) | 0.138 inch |
| Net weight | 0.169 g | | |

Temperatures

| | |
|-----------------------------|--------------|
| Operating temperature range | -40...100 °C |
|-----------------------------|--------------|

General data

| | | | |
|--|-------------------------------|-----------|--|
| Application/manufacture | Weidmueller | | |
| Colour | white | | |
| Colour of printing | black | | |
| Material | Polyamide 66 | | |
| Material colour according to resistance code | 9 | | |
| Number of markers per combination | 1 MultiCard = Terminal marker | | |
| Number of markers per packaging unit | Form of supply | MultiCard | |
| Operating temperature range | -40...100 °C | | |
| Operating temperature range, max. | 100 °C | | |
| Operating temperature range, min. | -40 °C | | |
| Orientation of print | vertical | | |
| Printed characters | Numbers | | |
| Printing method | MC Laser | | |
| UL 94 flammability rating | V-2 | | |
| Width | 3.5 mm | | |

Connector markers

| | |
|-----------------|--------|
| Pitch in mm (P) | 3.5 mm |
|-----------------|--------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000761 | ETIM 7.0 | EC000761 |
| ETIM 8.0 | EC000761 | ETIM 9.0 | EC000761 |
| ECLASS 9.0 | 27-14-11-37 | ECLASS 9.1 | 27-14-11-37 |
| ECLASS 10.0 | 27-14-11-37 | ECLASS 11.0 | 27-28-11-01 |
| ECLASS 12.0 | 27-28-11-01 | ECLASS 13.0 | 27-28-11-01 |
| ECLASS 14.0 | 27-28-11-01 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|-----------------------------|--|
| Product Change Notification | Technical change to MultiCard material - DE Technical change to MultiCard material - EN |
| Catalogues | Catalogues in PDF-format |

Creation date November 26, 2024 12:40:02 PM CET

Catalogue status 26.11.2024 / We reserve the right to make technical changes.

Data sheet

DEK 5/3,5 MC FSZ 1-10

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Drawing

