



YH6C6C, Copper Compression H-Tap, Run: #6-10 AWG, Tap: #6-14 AWG, Tin Plated

By Burndy
Catalog # [YH6C6C](#)



Copper Compression H Tap, Tin Plated, Accommodating the following wire sizes - Run (Main): 6 AWG-10 AWG Class B,C, 6 AWG-10 AWG Class I, DLO, Tap 1: 6 AWG-14 AWG Class B,C, 6 AWG-14 AWG Class I, DLO. See sale drawing for metric wire size accommodates

Features

- Uninsulated compression H-tap connector, tin-plated
- Designs with more than one tap wire groove require installers to utilize a minimum of one Main (Run) and one Tap groove, other grooves can be left empty
- 'Third Hand' is a string provided with the H-tap connector and is used to wrap the wire while being inserted into the run and tap grooves
- H-tap connectors can be purchased separately or kitted with covers
- YH is connector sold separately without cover
- YH-WC is kitted H-tap connector and black cover
- YH-WCC is kitted H-tap connector and clear cover

Application

Wire Tap

General

Catalog Number	YH6C6C
Color Code	Orange
Connector Type	H-TAP
Die Index	BG
EU RoHS Indicator	Yes
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	CRIMPIT
Temperature Rating	194
Trade Name	CRIMPIT™
Type	Compression Taps
UPC	781810042373
UPC 12 Digit	7818100423733

Dimensions

Dimension - Height inch	0.81 in
Dimension - L Length Overall mm	15 mm

Dimension - Length Overall inch	0.60 in
Dimension - Strip Length inch	3/4
Dimension - Width fraction	.39 in
Dimension - Width inch	0.81 in

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper Flex G Run	8;7;6
Conductor - Copper Flex G Run Range	8-6
Conductor - Copper Flex G Tap	14;8;7;6
Conductor - Copper Flex G Tap Range	14-6
Conductor - Copper Flex H Run	6 AWG
Conductor - Copper Flex H Run Range	6 AWG
Conductor - Copper Flex H Tap	14;8;7;6
Conductor - Copper Flex H Tap Range	14-6
Conductor - Copper Flex I Run	6 AWG-10 AWG
Conductor - Copper Flex I Tap	14;8;7;6
Conductor - Copper Flex I Tap Range	6 AWG-14 AWG
Conductor - Copper Flex K Run	8;7;6
Conductor - Copper Flex K Tap	14;8;7;6
Conductor - Copper Flex M Run	8;7;6
Conductor - Copper Flex M Tap	14;8;7;6
Conductor - Copper Str Run	10;9;8;7;6
Conductor - Copper Str Run Range	6 AWG-10 AWG
Conductor - Copper Str Tap	14;12;10;9;8;7;6
Conductor - Copper Str Tap Range	6 AWG-14 AWG
Conductor - Material	COPPER
Conductor Type	CODE/FLEX

Certifications And Compliance

Buy American Compliant	Contact Manufacturer
Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Certified Listed	Buy American Act Compliant (All status valid till December 2024)
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	150
Minimum Pack Quantity	1
Pallet Quantity	13500

Product Assets

- Catalogs - BURNDY Master Catalog - Section C - Compression Connections
- Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
- Customer Notices - Prop 65 Notice
- Interactive Catalog - BURNDY Full-Line Digital Catalog
- Product Cross Section Image(s) - BUR_YH_LINEART
- Sales Drawings - SD..206566-01
- Specifications - YH6C6C



A Hubbell brand