



Overview

Lead time	Usually in Stock
-----------	------------------



General

Provided Equipment	Installation guide Rack Mounting brackets
--------------------	--

Physical

Cable length	12 ft (3.66 m)
Color	Black
Depth	2.24 in (5.7 cm)
Height	1.73 in (4.4 cm)
Product Weight	5.51 lb(US) (2.5 kg)
Width	17.60 in (44.7 cm)

Input

Line Rated Current	16 A
Input current limits	20 A
Load Capacity	3328 VA
Input Frequency	50/60 Hz
Plug standard	NEMA L6-20P
Nominal Input Voltage	200 V 208 V 230 V

Output

Number of power socket outlets	12 IEC 60320 C13
--------------------------------	------------------

Conformance

Product Certifications	CUL Listed UL Listed
Standards	UL 60950

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	00731304213048
Package weight(Lbs)	8.02 lb(US) (3.64 kg)

Packing Units

Package 1 Height	2.76 in (7 cm)
Package 1 width	18.27 in (46.4 cm)
Package 1 Length	9.02 in (22.9 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------