



Main

Power Rating	1500 VA
Primary Voltage	600 V 575 V 550 V
Secondary Voltage	110/115/120 V

Complementary

Fuse type	0.41 x 1.50 in CC top
Temperature rise	115 °C
Height	7.46 in (189.48 mm)
Width	7.06 in (179.32 mm)
Depth	5.81 in (147.57 mm)
Material	Copper winding

Environment

Product Certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239 CE
Insulation temperature	356 °F (180 °C)

Ordering and shipping details

Category	16207 - 9070 TF (NOT T) MTO
Discount Schedule	CP8
GTIN	785901755128
Nbr. of units in pkg.	1
Package weight(Lbs)	34.00 lb(US) (15.422 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.90 in (27.686 cm)
Package 1 width	11.80 in (29.972 cm)
Package 1 Length	14.40 in (36.576 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------