2S82F

Transformer, buck boost, encapsulated, 2kVA, 1 phase, 240x480V primary, 24/48V secondary, NEMA 3R, 115C rise





Main

Widin	
Product	Buck and Boost Transformer
Enclosure Code	9A
Enclosure Type	NEMA 3R
Insulation Temperature	356 °F (180 °C)
Primary Voltage	240 x 480 V
Power Rating	2 kVA
Secondary Voltage	24/48 V
Temperature Rise	115 °C

Ordering and shipping details

Category	16265-BUCK & BOOST	
Discount Schedule	PE2	
GTIN	785901993506	
Returnability	Yes	
Country of origin	US	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.70 in (24.638 cm)
Package 1 Width	11.10 in (28.194 cm)
Package 1 Length	12.50 in (31.75 cm)
Package 1 Weight	49.50 lb(US) (22.453 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Warranty 18 months