

TUFF-SEAL™

RSR SERIES ALUMINUM CORD GRIPS



RSR Series Straight Aluminum Cord Grips (CONTINUED FROM PAGE G-1)

For applications known for their severe conditions – such as oil and gas, marine, food & chemical processing – RSR Cord Grips are

available in nickel-plated aluminum. Providing exceptional corrosion resistance and high wear resistance, nickel-plated connectors also feature an attractive finish similar to that of polished stainless steel.

Tuff Seal RSR Cord Grips protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.

NOTES

Accessories

Locknuts and O-Rings: Pages G-18

Special Configurations

Special configurations and materials are available.

Consult factory.

All wire mesh is stainless steel.


Dimension & certification information on pages G-34 & G-36 in Tuff-Seal Technical Reference.

G



Nickel-plated aluminum:
Cord grips available in nickel-plated aluminum. Add "N" to end of prefix. (ex: RSR-309 becomes RSRN-309)

COMPLETE ASSEMBLY PART NUMBERS



Conduit Size (NPT)	Cable Range	Cord Grip	Cord Grip With Mesh
1"			
	.438 – .562	RSR-309	RSR-309-E
	.562 – .625	RSR-310	RSR-310-E
	.562 – .688	RSR-311	RSR-311-E
	.625 – .750	RSR-312	RSR-312-E
	.688 – .812	RSR-313	RSR-313-E
	.750 – .875	RSR-314	RSR-314-E
	.812 – .938	RSR-315	RSR-315-E
	.875 – 1.000	RSR-316*	RSR-316-E
	.875 – 1.000	RSR-3516	RSR-3516-E
	1.000 – 1.125	RSR-3518*	RSR-3518-E
	1.125 – 1.250	RSR-3520*	RSR-3520-E
	1.250 – 1.375	RSR-3522*	RSR-3522-E
1 1/4"			
	.562 – .688	RSR-411	—
	.688 – .812	RSR-413	—
	.750 – .875	RSR-414	—
	.875 – 1.000	RSR-416	RSR-416-E
	1.000 – 1.125	RSR-418	RSR-418-E
	1.125 – 1.250	RSR-420*	RSR-420-E
	1.250 – 1.375	RSR-422*	RSR-422-E
1 1/2"			
	.562 – .688	RSR-511	—
	.688 – .812	RSR-513	—
	.750 – .875	RSR-514	—
	.875 – 1.000	RSR-516	RSR-516-E
	1.000 – 1.125	RSR-518	RSR-518-E
	1.125 – 1.250	RSR-520	RSR-520-E
	1.250 – 1.375	RSR-522	RSR-522-E
	1.250 – 1.375	RSR-5622	RSR-5622-E
	1.438 – 1.562	RSR-5625*	RSR-5625-E
	1.562 – 1.688	RSR-5627*	RSR-5627-E
	1.688 – 1.812	RSR-5629*	RSR-5629-E
2"			
	1.250 – 1.375	RSR-622	RSR-622-E
	1.312 – 1.437	RSR-623	RSR-623-E
	1.438 – 1.562	RSR-625	RSR-625-E
	1.562 – 1.688	RSR-627	RSR-627-E
	1.688 – 1.812	RSR-629	RSR-629-E
	1.688 – 1.812	RSR-6729	RSR-6729-E
	1.812 – 1.938	RSR-6731	RSR-6731-E
	1.938 – 2.062	RSR-6733*	RSR-6733-E
	2.062 – 2.188	RSR-6735*	RSR-6735-E
	2.188 – 2.312	RSR-6737*	RSR-6737-E
	2.312 – 2.438	RSR-6739*	RSR-6739-E
2 1/2"			
	1.688 – 1.812	RSR-729	RSR-729-E
	1.812 – 1.938	RSR-731	RSR-731-E
	1.938 – 2.062	RSR-733	RSR-733-E
	2.062 – 2.188	RSR-735	RSR-735-E
	2.188 – 2.312	RSR-737	RSR-737-E
	2.312 – 2.438	RSR-739*	RSR-739-E
3"			
	1.688 – 1.812	RSR-8729	RSR-8729-E
	1.812 – 1.938	RSR-8731	RSR-8731-E
	1.938 – 2.062	RSR-8733	RSR-8733-E
	2.062 – 2.188	RSR-8735	RSR-8735-E
	2.188 – 2.312	RSR-8737	RSR-8737-E
	2.312 – 2.438	RSR-8739*	RSR-8739-E
	2.437 – 2.625	RSR-901	RSR-901-E
	2.625 – 2.812	RSR-902	RSR-902-E
	2.812 – 3.000	RSR-903	RSR-903-E

*Cable may have to be stripped to pass through the bore of the body