

**PTS 4****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Power distribution using uncut cables with cross-sections from 1.5 to 6 mm<sup>2</sup>.

Power supply / T-branch tap via PUSH IN connection (0.5 to 10 mm<sup>2</sup>) and/or plug-in connection (0.5 to 4 mm<sup>2</sup>).

Coloured markings provide clear assignment of wires.

- Power supply
- Power distribution
- Power branching

**General ordering data**

Version	Field Power® plug-in connector, 3-phase AC, IP20, Polyamide, PUSH IN, Number of poles : 5
Order No.	<a href="#">1952120000</a>
Type	PTS 4
GTIN (EAN)	4032248632909
Qty.	10 pièce(s)

## PTS 4

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Caractéristiques techniques

## Dimensions and weights

Depth	36,15 mm	Depth (inches)	1,423 inch
Height	27,3 mm	Height (inches)	1,075 inch
Width	55,45 mm	Width (inches)	2,183 inch
Net weight	34,3 g		

## Temperatures

Storage temperature	-40 °C...85 °C	Operating temperature	-40 °C...80 °C
---------------------	----------------	-----------------------	----------------

## Approbations

Certificate No. (cURus)	E60693	Institute (cURus)	CURUS
-------------------------	--------	-------------------	-------

## Clamping capacity, PUSH IN connection

Blade size, PUSH IN connection	3.0 x 0.5 mm	Clamping range, max. PUSH IN connection	4 mm <sup>2</sup>
Clamping range, min. PUSH IN connection	0,5 mm <sup>2</sup>	Cross-section for connected wire PUSH IN connection, solid, min.	0,5 mm <sup>2</sup>
Cross-section for connected wire, PUSH IN connection, solid, max.	4 mm <sup>2</sup>	Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/1, PUSH IN connection, max.	4 mm <sup>2</sup>
Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/1, PUSH IN connection, min.	0,5 mm <sup>2</sup>	Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/4, PUSH IN connection, max.	4 mm <sup>2</sup>
Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/4, PUSH IN connection, min.	0,5 mm <sup>2</sup>	Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/1, PUSH IN connection, max.	4 mm <sup>2</sup>
Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/1, PUSH IN connection, min.	0,5 mm <sup>2</sup>	Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/4, PUSH IN connection, max.	4 mm <sup>2</sup>
Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/4, PUSH IN connection, min.	0,5 mm <sup>2</sup>	Cross-section for connected wire, flexible, PUSH IN connection, max.	4 mm <sup>2</sup>
Cross-section for connected wire, flexible, PUSH IN connection, min.	0,5 mm <sup>2</sup>	Finely-stranded flexible, max. PUSH IN connection	4 mm <sup>2</sup>
Finely-stranded flexible, min. PUSH IN connection	0,5 mm <sup>2</sup>	Stripping length, PUSH IN connection	12 mm
Wire connection cross section, stranded, PUSH IN connection, max.	4 mm <sup>2</sup>	Wire connection cross section, stranded, PUSH IN connection, min.	0,5 mm <sup>2</sup>

## PTS 4

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Caractéristiques techniques

## Clamping capacity

Connection data - plug-in connector	Wire connection method	PUSH IN	
	Blade size of operating tool	3.0 x 0.5 mm	
	Stripping length	12 mm	
	Number of poles	5	
	Conductor connection cross-section, solid, max.	4 mm <sup>2</sup>	
	Conductor connection cross-section, solid, min.	0,5 mm <sup>2</sup>	
	Conductor connection cross-section, stranded, max.	4 mm <sup>2</sup>	
	Conductor connection cross-section, stranded, min.	0,5 mm <sup>2</sup>	
	Conductor connection cross-section, finely stranded, max.	4 mm <sup>2</sup>	
	Conductor connection cross-section, finely stranded, min.	0,5 mm <sup>2</sup>	
	Conductor connection cross-section, finest stranded, max.	4 mm <sup>2</sup>	
	Conductor connection cross-section, finest stranded, min.	0,5 mm <sup>2</sup>	
	Conductor connection cross-section with wire end ferrule	Type of wire end ferrule	12 mm with plastic collar
		Standard	DIN 46228/1
		Cross-section, min.	0,5 mm <sup>2</sup>
		Cross-section, max.	4 mm <sup>2</sup>
		Type of wire end ferrule	12 mm with plastic collar
		Standard	DIN 46228/4
		Cross-section, min.	0,5 mm <sup>2</sup>
		Cross-section, max.	4 mm <sup>2</sup>
		Type of wire end ferrule	8 mm with plastic collar
		Standard	DIN 46228/1
		Cross-section, min.	0,5 mm <sup>2</sup>
		Cross-section, max.	4 mm <sup>2</sup>
		Type of wire end ferrule	8 mm with plastic collar
		Standard	DIN 46228/4
		Cross-section, min.	0,5 mm <sup>2</sup>
Cross-section, max.		4 mm <sup>2</sup>	
Type of wire end ferrule	Twin wire-end ferrules		
Cross-section, min.	0,5 mm <sup>2</sup>		
Cross-section, max.	4 mm <sup>2</sup>		

## General data

Insulating material	Polyamide	Silicone	No
Colour	black	Protection degree	IP20
UL 94 flammability rating	V-0	Type of mounting	Plugged
Can be coded	Yes, Coded on PE	Test point	2 mm
Voltage type	3-phase AC	Number of poles	5
Number of connections / pole	1	Wire connection method	PUSH IN
Conductor outlet direction	90°		

## PTS 4

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Caractéristiques techniques

## Rated data acc. to IEC

Rated data acc. to IEC for plug-in connector	Voltage type	AC
	Number of phases	3
	Standard	IEC 60947-7-1, IEC 60947-7-2, IEC 61984
	Rated voltage	690 V
	Rated impulse withstand voltage	8 kV
	Rated current (3 loaded poles)	32 A
	Rated current (4 loaded poles)	25 A

## Rated data acc. to UL

Rated data acc. to UL for plug-in connector	Standard	UL 1059
	Note	for use with UL-listed TC-ER cables
	Conductor connection cross-section, AWG, max.	AWG 12
	Conductor connection cross-section, AWG, min.	AWG 16
	Rated voltage	600 V
	Rated current	20 A

## Classifications

ETIM 6.0	EC002943	ETIM 7.0	EC002943
ETIM 8.0	EC002943	ETIM 9.0	EC002943
ECLASS 9.0	27-44-02-92	ECLASS 9.1	27-44-03-90
ECLASS 10.0	27-44-02-92	ECLASS 11.0	27-44-02-92
ECLASS 12.0	27-44-02-92	ECLASS 13.0	27-44-02-92
ECLASS 14.0	27-44-02-92		

## Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

## Approvals

Approvals



ROHS	Conform
UL File Number Search	UL Website
Certificate No. (cURus)	E60693

## Downloads

Approval/Certificate/Document of Conformity	<a href="#">UL Certificate FieldPower® Box and accessories</a> <a href="#">UL Certificate FieldPower® terminals and plug-in connectors</a> <a href="#">Manufacturer's Declaration FieldPower® plug-in connectors and HQ adapters</a>
Engineering Data	<a href="#">CAD data – STEP</a>
User Documentation	<a href="#">Manual FieldPower® PTS 4 and PTDS 4</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>

**Fiche de données**

**PTS 4**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Dessins**

