



Main

Range	Mureva
Range of Product	Mureva lights
Product or Component Type	Floodlight
Device Application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

Complementary

Type of Installation	Outdoor
Total system power	50 W
Light source	LED
[Ue] rated operational voltage	120 V AC
Power factor	0.9
Colour rendering index	R _a =80
Luminous flux	5250 lm
Bulb lifespan	50000 h
Colour temperature	4000 K
Colour tint	black
Provided Equipment	Sensor
Beam angle	110 °
Shape	Rectangular
Height	8.48 in (215.4 mm)
Width	726.38 ft (221.4 m)
Depth	1.22 in (31 mm)
Net Weight	2.34 lb(US) (1.06 kg)

Environment

Environmental characteristic	Weatherproof
IP Degree of Protection	IP44
IK degree of protection	IK04
Ambient Air Temperature for Operation	-22...113 °F (-30...45 °C)

Ordering and shipping details

Category	18160-MODICON M340
Discount Schedule	PC34
GTIN	3606489903374
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7.0 cm)
Package 1 Width	9.65 in (24.5 cm)
Package 1 Length	9.65 in (24.5 cm)
Package 1 Weight	2.68 lb(US) (1.216 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	10
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	28.36 lb(US) (12.863 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Height	29.53 in (75.0 cm)
Package 3 Width	31.50 in (80.0 cm)
Package 3 Length	47.24 in (120.0 cm)
Package 3 Weight	253.32 lb(US) (114.904 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information