VHU362DSGL

Safety switch, heavy duty, unfused, viewing window, NEMA 4X, 600V, 60A, 3 pole, ground lugs



Main Product Single Throw Safety Switch **Duty Rating** Heavy duty **Device Application** Heavy application Disconnect Type Non-fusible disconnect Field installed kit available Factory Installed Neutral Number of Poles **Current Rating** 60 A 600 V AC/DC Voltage Rating Enclosure Rating NEMA 4X stainless steel 304 Motor power hp 10 Hp at 240 V AC 50/60 Hz for 1 phase motors 20 Hp at 240 V AC 50/60 Hz for 3 phase motors 25 Hp at 480 V AC 50/60 Hz for 1 phase motors 50 Hp at 480 V AC 50/60 Hz for 3 phase motors

10 Hp at 250 V DC 30 hp at 600 V DC

30~Hp at 600~V AC 50/60 Hz for 1 phase motors 60~Hp at 600~V AC 50/60 Hz for 3 phase motors

Complementary

Surface
Lugs
3-wire
AWG 14AWG 3 copper AWG 12AWG 3 aluminium
50 Lbf.In (5.65 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)
7.26 in (184.40 mm)
8.92 in (226.57 mm)
16.93 in (430.02 mm)
19.84 lb(US) (9 kg)
Factory installation
Suitable service entrance for USA Suitable service entrance for Mexico

Environment

Certifications	UL listed file E2875	
----------------	----------------------	--

Ordering and shipping details

00010-H&HU SW,2&3P,N4,SS,30-200A
DE1
3606485894683
No
US

Packing Units

PCE	
1	
7.37 in (18.732 cm)	
11.00 in (27.94 cm)	
18.69 in (47.466 cm)	
20.94 lb(US) (9.5 kg)	
	1 7.37 in (18.732 cm) 11.00 in (27.94 cm) 18.69 in (47.466 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations