



## KWPL430 - 4,000 Lumen Range 120-277 Volt LED Wallpack Fixture

By Killark  
Catalog # KWPL430

4,000 Lumen Range 120-277 Volt LED Wallpack Fixture

### Features

- Aluminum with Bronze finish 1/2" hub on either side for conduit entry.
- Suitability for 55°C ambient, 90°C supply wire required.
- Lens thermal shock and impact resistant prismatic borosilicate glass.
- Two Hubbell Guard® Corrosion resistant hex head fasteners provide water-tight seal for door gasket.
- Optional factory installed photocells & fusing available.

### General

Catalog Number	KWPL430
EU RoHS Indicator	Contact Manufacturer
Lumen Range	2,001-5,000 lm
Lumens	4436
Series	KWPL
UPC	783936139852

### Dimensions



\*Representative Image

Hub Size	1/2"
Weight	14 lb

### Electrical Ratings

Voltage Rating	120-277 VAC
----------------	-------------

### Certifications And Compliance

Hazardous Rating(s)	<ul style="list-style-type: none"><li>• Class I, Division 2, Groups A, B, C, D</li><li>• Class I, Zone 2, Groups IIC, IIB, IIA</li></ul>
Nema Rating	4X

### Product Assets

- [Catalogs - Killark Catalog](#)
- [Photometry - KIL\\_KWPL430](#)
- [Specifications - KWPL Series LED Wallpack Specification Sheet](#)
- [Specifications - KWPL430 Specification Sheet English](#)
- [Specifications - KWPL430 Specification Sheet French](#)