

Rittal – The System.

Faster – better – everywhere.

Wall-Mounted Housing WM – WM 1077.250

Date : Jan 29, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-Mounted Housing WM – WM 1077.250 - WM303008NC

erstellt am : 29.01.2015 build on www.rittal.com/us-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert
Packaging unit:	1 pc(s).
EAN:	4028177532724

Product features

Dimensions:	Height: 760 mm (30 ") Width: 760 mm (30 ") Depth: 210 mm (8.3 ")
-------------	--

Mounting plate:	Height: 730 mm (29 ") Width: 704 mm (28 ")
------------------------	---

Weight:	40 kg (88.2 lb.)
----------------	--------------------

Approvals

Approvals:	 UL (EN)
-------------------	---

Downloads

Data sheets:	 Graphics (US)
---------------------	---

Documentation:	 Info sheet (US)  Load brochure (US)
-----------------------	---

CAD drawings:	Request
----------------------	-------------------------

2015 © Rittal Corporation