

C-HB-B-RD Series

Round LED UFO High Bay Light

Replaces up to 400W PSMH

C-LITE
LED LIGHTING

THE HIGH BAY MADE FOR YOU

Our cETLus Listed Round LED UFO High Bay Light delivers up to 140 lumens per watt and features an integrated hook for easy mounting. Sold separately, accessories include a plug-and-play motion sensor with a remote to control your settings. It comes with an emergency backup, as well as high voltage options for more demanding applications.



PRODUCT SPECIFICATIONS

OVERVIEW

- Max. Delivered Lumens: 14,000 **(14L)**; 21,000 **(20L)**; 27,000 **(27L)**; 33,600 **(33L)**
- CRI: ≥ 80
- CCT: 4000K or 5000K
- Input Power: 100W **(14L)**; 150W **(20L)**; 200W **(27L)**; 240W **(33L)**
- Dimmable: 0-10V to 10% with UL (120-277V) voltage only. UH (347-480V) luminaires may only be dimmed using the motion sensor accessory
- Operating Temperature Range: **(w/o EB)** -4°F to 122°F (-20°C to 50°C); **(w/EB)** 32°F to 122°F (0°C to 50°C)
- Estimated L₇₀ Lifetime @ 25°C (77°F): >75,000 hours
- Power Factor: >.9 at full load
- Total Harmonic Distortion: <20% at full load
- Limited Warranty: 5-Year*
- Replaces: 250W PSMH **(14L)**; 320W PSMH **(20L)**; 400W PSMH **(27L, 33L)**

FEATURES	RECOMMENDED USE	INPUT VOLTAGE
<ul style="list-style-type: none">• 140 LPW• Wide variety of accessories sold separately — including a plug-and-play motion sensor with a remote to control the settings• Emergency Battery Backup (EB) and high voltage options• IP65 rated• FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions	<ul style="list-style-type: none">• Auto Dealerships• Commercial• Gymnasium• Industrial• Manufacturing• Storage Facilities• Warehouses	<ul style="list-style-type: none">• UL: Universal (120-277V)• UH: High voltage (347-480V)

CERTIFICATIONS:

 **CA RESIDENTS WARNING:** Cancer and Reproductive Harm – www.p65warnings.ca.gov




C-HB-B-RD Series

ORDERING INFORMATION


Example SKU: C-HB-B-RD-20L-50K-UL-WH-EB

C-HB	B	RD					
PRODUCT	SERIES	STYLE	LUMEN PACKAGE	CCT	VOLTAGE	COLOR	EMERGENCY BATTERY BACKUP OPTION
C-HB High Bay	B	RD Round	14L 14,000 Lumens 20L 21,000 Lumens 27L 27,000 Lumens 33L 33,600 Lumens	40K Neutral White (4000K) 50K Cool White (5000K)	UL Universal 120-277V UH High 347-480V (Available for 20L, 27L and 33L options, only in white housing)	WH White BK Black	[BLANK] w/out Emergency Battery Backup Option EB w/ Emergency Battery Backup Option (Available for 120-277V versions only) — Provides 40W (~5400 lumens) and 90 minutes of emergency operation


C-HB-B-RD-14L




C-HB-B-RD-20L




C-HB-B-RD-27L




C-HB-B-RD-33L




C-HB-B-RD-14L-EB




C-HB-B-RD-20L-EB



C-HB-B-RD-27L-EB



C-HB-B-RD-33L-EB



C-HB-B-RD Series

SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
(14L) 8-3/4" (222mm) Dia x 6-1/8" (156mm) H (20L) 10-1/4" (260mm) Dia x 6-1/2" (165mm) H (27L) 11-3/4" (299mm) Dia x 6-1/2" (165mm) H (33L) 14-1/4" (362mm) Dia x 6-1/2" (165mm) H	(14L) 5.51 lbs. (20L) 6.45 lbs. (27L) 7.72 lbs. (33L) 9.92 lbs.	(14L) 15 - 20 feet (20L) 15 - 25 feet (27L) 20 - 30 feet (33L) > 30 feet	1 to 1-1/2 times the mounting height
(14L w/EB) 8-3/4" (222mm) Dia x 21-5/8" (550mm) H (20L w/EB) 10-1/4" (260mm) Dia x 22" (559mm) H (27L w/EB) 11-3/4" (299mm) Dia x 22" (559mm) H (33L w/EB) 14-1/4" (362mm) Dia x 22" (559mm) H	(14L w/EB) 11.02 lbs. (20L w/EB) 14.11 lbs. (27L w/EB) 15.21 lbs. (33L w/EB) 17.42 lbs.	(14L w/EB) 15 - 20 feet (20L w/EB) 15 - 25 feet (27L w/EB) 20 - 30 feet (33L w/EB) > 30 feet	1 to 1-1/2 times the mounting height

FIXTURE SPECIFICATIONS

HOUSING	Die-cast aluminum with a durable, black or white powder-coat finish
LENS ASSEMBLY	Clear polycarbonate
MOUNTING	Integrated hook, pendant mounting option available; included 6-foot power cord
ELECTRICAL	Non-EB models: 6 ft power cord, 12 in dimming cord EB models: 6 ft power cord, 6 ft dimming cord UH models: 6 ft power cord, no dimming cord (may only be dimmed using the motion sensor accessory)

LUMINAIRE AND ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	ESTIMATED L ₇₀ LIFETIME @ 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION
-4°F to 122°F (-20°C to 50°C) (w/o EB) 32°F to 122°F (0°C to 50°C) (w/ EB)	>75,000 hours	>.9 at full load	<20% at full load

SERIES	REPLACES	LUMEN OUTPUT	SYSTEM WATTS	CURRENT DRAW (AMPS)					
				120V	208V	240V	277V	347V	480V
C-HB-B-RD-14L	250W PSMH	14,000	100W	0.83	0.53	0.46	0.4	N/A	N/A
C-HB-B-RD-20L	320W PSMH	21,000	150W	1.39	0.8	0.69	0.6		
C-HB-B-RD-27L	400W PSMH	27,000	200W	1.85	1.07	0.93	0.8		
C-HB-B-RD-33L		33,600	240W	2.22	1.28	1.11	0.96		
C-HB-B-RD-20L-UH	320W PSMH	21,000	150W	N/A	N/A	N/A	N/A	0.48	0.35
C-HB-B-RD-27L-UH	400W PSMH	27,000	200W					0.64	0.46
C-HB-B-RD-33L-UH		33,600	240W					0.77	0.56

WARRANTY AND CERTIFICATIONS

WARRANTY	cETLus LISTED	DLC
5-Year Limited*	Wet Listed	Premium

C-HB-B-RD Series

ACCESSORIES

	ALUMINUM REFLECTOR SMALL SKU: C-HB-B-ACC-AR-SM USE: Aluminum reflector for the 100W and 150W C-HB-B-RD Series.		WIRE GUARD SMALL SKU: C-HB-B-ACC-WG-SM USE: Wire guard for the 100W & 150W C-HB-B-RD Series. Additional reflector is required.
	PRISMATIC REFLECTOR SMALL SKU: C-HB-B-ACC-PR-SM USE: Clear prismatic polycarbonate reflector for the 100W and 150W C-HB-B-RD Series.		WIRE GUARD LARGE SKU: C-HB-B-ACC-WG-LG USE: Wire guard for the 200W & 240W C-HB-B-RD Series. Additional reflector is required.
	ALUMINUM REFLECTOR LARGE SKU: C-HB-B-ACC-AR-LG USE: Aluminum reflector for the 200W and 240W C-HB-B-RD Series.		MOTION SENSOR SKU: C-HB-B-ACC-MS-UL USE: Plug-and-play microwave motion sensor for C-HB-B-RD Series. Additional remote required for programming sensor settings.
	PRISMATIC REFLECTOR LARGE SKU: C-HB-B-ACC-PR-LG USE: Clear prismatic polycarbonate reflector for the 200W and 240W C-HB-B-RD Series.		PENDANT MOUNT WHITE SKU: C-HB-B-ACC-PM-WH USE: Pendant mount adapter for C-HB-B-RD Series, 3/4" threaded NPT for conduit pendant mounting, white.
	DROP LENS SMALL SKU: C-HB-B-ACC-DL-SM USE: Clear prismatic polycarbonate drop lens for the 100W and 150W C-HB-B-RD Series. Additional reflector is required.		PENDANT MOUNT BLACK SKU: C-HB-B-ACC-PM-BK USE: Pendant mount adapter for C-HB-B-RD Series, 3/4" threaded NPT for conduit pendant mounting, black.
	CONICAL LENS SMALL SKU: C-HB-B-ACC-CL-SM USE: Clear prismatic polycarbonate conical lens for the 100W and 150W C-HB-B-RD Series. Additional reflector is required.		MOTION SENSOR REMOTE SKU: C-HB-B-ACC-MS-REMOTE USE: Remote for programming plug-and-play motion sensor. Remote can control multiple fixture sensors. For use with C-HB-B-RD Series.
	DROP LENS LARGE SKU: C-HB-B-ACC-DL-LG USE: Clear prismatic polycarbonate drop lens for the 200W and 240W C-HB-B-RD Series. Additional reflector is required.		DIMMING ACCESSORY 0-10V DIMMING SKU: C-HB-B-ACC-DIMKIT USE: Dimming accessory kit for 0-10V dimming of the fixture when using a wall switch. Contains 6-foot cord as well as male and female connectors. For use with non-EB models only. UH (347-480V) luminaires may only be dimmed using the motion sensor accessory.
	CONICAL LENS LARGE SKU: C-HB-B-ACC-CL-LG USE: Clear prismatic polycarbonate conical lens for the 200W and 240W C-HB-B-RD Series. Additional reflector is required.		

© 2022 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. C-Lite and the C-Lite logo are registered trademarks of Cree Lighting. The cETLus Listed Intertek logo is a trademark of Intertek Testing Services NA, Inc. The DLC QPL logo and the DLC QPL Premium logo are registered trademarks of Northeast Efficiency Partnerships, Inc.

US: creelighting.com, e-conolight.com

Distribution/Sales: 855-617-2733 Customer Service: 888-243-9445

Rev. Date: 05/13/2022

For informational purposes only. Content is subject to change. *See creelighting.com/resources/warranties for details

C-LITE
LED LIGHTING