



Main

| | |
|----------------------------|---|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch lever |
| Device short name | ZCY |
| Product compatibility | XCKT XCKP XCKD |
| Associated head | ZCE01 ZCE05 |
| Movement of operating head | Rotary |
| Type of operator | Roller lever spring return thermoplastic roller diameter 50 mm) |
| Tracks | No track |
| Type of approach | Lateral approach |

Complementary

| | |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With |

Environment

| | |
|---------------------------------------|----------------------------|
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------|------------------------|
| Package 1 Weight | 0.06 lb(US) (0.027 kg) |
| Package 1 Height | 0.200 dm |

| | |
|------------------|----------|
| Package 1 width | 0.650 dm |
| Package 1 Length | 0.500 dm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|