



**ZCK E66**

**Main**

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJD39 ZCKJ6H29 ZCKJ9H29 ZCKJ8 ZCKJ5H7 ZCKJD37H29 ZCKJ2H7 ZCKJ41 ZCKJ1 ZCKJD31H7 ZCKJ21 ZCKJ5 ZCKJD35H7 ZCKJ2 ZCKJD39H29 ZCKJ7 ZCKJ2H29 ZCKJ8H29 ZCKJ41H7 ZCKJ4H7 ZCKJ9 ZCKJ11H7 ZCKJ6 ZCKJ8H7 ZCKJ11H29 ZCKJ9H7 ZCKJ1H29 ZCKJ1H7 ZCKJ5H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJD35H29  
 ZCKJD31H29  
 ZCKJ6H7  
 ZCKJD37  
 ZCKJ41H29  
 ZCKJ4H29  
 ZCKJD39H7  
 ZCKJ21H7  
 ZCKJ7H29  
 ZCKJD35  
 ZCKJD37H7  
 ZCKJ7H7  
 ZCKJD31  
 ZCKJ21H29  
 ZCKJ4  
 ZCKJ11

Movement of operating head	Linear
Type of operator	End plunger spring return metal ball bearing mounted)
Type of approach	Multi-directional approach

### Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

### Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.19 oz (147 g)
Package 1 Height	1.65 in (4.2 cm)
Package 1 width	1.85 in (4.7 cm)
Package 1 Length	3.39 in (8.6 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------