



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Rotary head
Product compatibility	XCKT XCMD XCKP XCKD
Associated lever	ZCE61 ZCE71
Associated body	ZCP39 ZCMD81L2 ZCMD61M12 ZCMD29L1 ZCMD81L1 ZCD21M12 ZCD29 ZCP31 ZCMD37L5 ZCT21N12 ZCT28N12 ZCMD21L2 ZCT21G11 ZCP35 ZCMD39L1 ZCMD29L2 ZCD27 ZCD39 ZCD28 ZCMD21L1 ZCMD21L08U78 ZCT27P16 ZCP28 ZCP27

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCMD21L5
 ZCT26N12
 ZCMD21C12
 ZCD35
 ZCMD41L5
 ZCMD39L2
 ZCT27N12
 ZCMD21M12
 ZCD31
 ZCD29M12
 ZCMD25L1
 ZCP21
 ZCT25P16
 ZCT28G11
 ZCT25N12
 ZCMD29L5
 ZCMD69C12
 ZCD26
 ZCT28P16
 ZCP29M12
 ZCMD29C12
 ZCP37
 ZCP25
 ZCT27G11
 ZCMD21L08R12
 ZCP29
 ZCD37
 ZCMD41L2
 ZCT25G11
 ZCMD25L2
 ZCD21
 ZCP21M12
 ZCD25
 ZCT26P16
 ZCMD61C12
 ZCT26G11
 ZCMD81L5
 ZCP26
 ZCMD39L5
 ZCMD25L5
 ZCMD37L1
 ZCMD41L1
 ZCT21P16
 ZCMD37L2

Movement of operating head	Rotary
Type of operator	Stay put without operating lever stay put metal
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By specific cam
Positive opening	Without

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.12 lb(US) (0.054 kg)
Package 1 Height	0.160 dm
Package 1 width	0.320 dm
Package 1 Length	0.480 dm

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------