

## XVBC8M6

Indicator bank, Harmony XVB, illuminated unit, plastic, blue, 70mm, integral flash discharge tube, 10joule, 230V AC



### Main

|                                    |                                     |
|------------------------------------|-------------------------------------|
| Range of Product                   | Harmony XVB Universal               |
| Product or Component Type          | Indicator bank                      |
| Beacon or indicator bank unit type | Illuminated unit                    |
| Signalling type                    | Flashing                            |
| Mounting diameter                  | 2.76 in (70 mm)                     |
| Component name                     | XVBC                                |
| Material                           | Polycarbonate                       |
| Light source                       | Integral flash discharge tube, blue |
| Bulb type                          | Flash discharge tube                |
| [Us] rated supply voltage          | 230 V AC                            |
| Flash energy                       | 10 J                                |

### Complementary

|                                        |                                                                  |
|----------------------------------------|------------------------------------------------------------------|
| Assembly style                         | Customer assembly, up to 5 units                                 |
| Connections - terminals                | Screw clamp terminals, <= 1 x 1.5 mm <sup>2</sup> with cable end |
| [Ui] rated insulation voltage          | 250 V IEC 60947-1                                                |
| Nominal voltage limit                  | 0.85...1.1 Un IEC 60947-5-1                                      |
| Current consumption                    | < 280 mA AC                                                      |
| [Uimp] rated impulse withstand voltage | 4 kV IEC 60947-1                                                 |
| Flashing frequency                     | 1 Hz                                                             |
| CAD overall width                      | 2.76 in (70 mm)                                                  |
| CAD overall height                     | 6.18 in (157 mm)                                                 |
| CAD overall depth                      | 2.76 in (70 mm)                                                  |
| Net Weight                             | 0.69 lb(US) (0.315 kg)                                           |

### Environment

|                                     |                                                                      |
|-------------------------------------|----------------------------------------------------------------------|
| Product Certifications              | CCC[RETURN]EAC[RETURN]CSA C22-2 No 14[RETURN]UL 508                  |
| Standards                           | EN/IEC 60947-5-1                                                     |
| Protective treatment                | TC                                                                   |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C)                                           |
| Electrical shock protection class   | Class I on support tube IEC 61140<br>Class II on base unit IEC 61140 |
| IP degree of protection             | IP65 on fixing base XVBZ0. IEC 60529<br>IP66 on base unit IEC 60529  |
| NEMA degree of protection           | Type 4X UL indoor)                                                   |

### Packing Units

|                              |                    |
|------------------------------|--------------------|
| Unit Type of Package 1       | PCE                |
| Number of Units in Package 1 | 1                  |
| Package 1 Height             | 3.15 in (8.0 cm)   |
| Package 1 Width              | 3.15 in (8.0 cm)   |
| Package 1 Length             | 7.36 in (18.7 cm)  |
| Package 1 Weight             | 11.60 oz (329.0 g) |

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 2       | S03                    |
| Number of Units in Package 2 | 12                     |
| Package 2 Height             | 11.81 in (30.0 cm)     |
| Package 2 Width              | 11.81 in (30.0 cm)     |
| Package 2 Length             | 15.75 in (40.0 cm)     |
| Package 2 Weight             | 9.76 lb(US) (4.428 kg) |


### Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                           |
| REACH Regulation           | <a href="#"> REACH Declaration</a>             |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)                                                                      |
| Mercury free               | Yes                                                                                                                             |
| China RoHS Regulation      | <a href="#"> China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#"> Yes</a>                           |
| Environmental Disclosure   | <a href="#"> Product Environmental Profile</a> |
| Circularity Profile        | No need of specific recycling operations                                                                                        |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.    |

Indicator Bank with “Flash” Discharge Tube Unit

Dimensions

Below drawing shows the minimum configuration of the product. Select the number of stages according to the product characteristics in order to get b dimension.



- (1) Base unit XVBC07, to be ordered separately
- (2) Illuminated or audible signalling unit XVBC\*\*\*, to be ordered separately
- (3) “Flash” unit

| Number of illuminated or audible signalling units other than “flash” tube | b in mm | b in in. |
|---------------------------------------------------------------------------|---------|----------|
| 1                                                                         | 295     | 11.61    |
| 2                                                                         | 358     | 14.09    |
| 3                                                                         | 421     | 16.57    |
| 4                                                                         | 484     | 19.06    |