fiberglass



EXTRA-HEAVY DUTY FIBERGLASS STEP

Meets or exceeds CSA Grade 1A, ANSI Type 1A

- Durable non-conductive side rails in high visibility safety yellow Copolymer utility top for strength and durability Wide 3" slip-resistant serrated aluminum steps for safe climbing
- Inside spreader arms that are protected during storage/loading/transit
- Full rear "L" horizontal struts, Top and bottom struts reinforced with Zinc coated steel diagonal braces Reinforced with Zinc coated steel diagonal braces at top and bottom steps
- PVC rubber safety boots are heavy duty and provide rail protection and slip-resistance

| MODEL | SIZE | OPEN HEIGHT | HIGHEST STANDING HEIGHT | BASE WIDTH | BASE DEPTH | APPROX. WEIGHT lbs |
|-------|------|----------------|-------------------------------|---------------|---------------|--------------------------|
| 6903* | 3' | 34" | 11" | 17" | 24" | 12 |
| 6904 | 4' | 45" | 23" | 19" | 31" | 14 |
| 6905 | 5' | 56" | 34" | 20" | 36" | 17 |
| 6906 | 6' | 68" | 45" | 21" | 42" | 20 |
| 6907 | 7' | 79" | 56" | 22" | 48" | 23 |
| 6908 | 8' | 90" | 67" | 24" | 54" | 26 |
| 6910 | 10' | 113" | 90" | 26" | 66" | 37 |
| 6912 | 12' | 135" | 112" | 29" | 80" | 48 |

^{*}NON UTILITY TOP, STEP STOOL

HEAVY DUTY FIBERGLASS STEP

Meets or exceeds CSA Grade 1, ANSI Type 1

- Slip-resistant safety shoes

| MODEL | SIZE | OPEN HEIGHT | HIGHEST STANDING HEIGHT | BASE WIDTH | BASE DEPTH | APPROX. WEIGHT lbs |
|-------|------|----------------|-------------------------------|---------------|---------------|--------------------------|
| 6304 | 4' | 46" | 23" | 20" | 30" | 15 |
| 6305 | 5' | 57" | 34" | 21" | 34" | 18 |
| 6306 | 6' | 68" | 45" | 23" | 43" | 20 |
| 6307 | 7' | 79" | 56" | 24" | 44" | 23 |
| 6308 | 8' | 90" | 67" | 26" | 55" | 26 |







MEDIUM DUTY FIBERGLASS STEP

Meets or exceeds CSA Grade 2, ANSI Type 2

- Durable non-conductive fiberglass side rails in high visibility safety red Molded copolymer utility top for holding tools and paint accessories
- Fold down utility tray
- Wide 3" slip-resistant serrated aluminum steps for safe climbing Rugged outside Zinc coated steel spreader arms
- Reinforced with Zinc coated steel diagonal braces at top and bottom steps
- Slip-resistant safety shoes

| MODEL | SIZE | OPEN HEIGHT | HIGHEST STANDING HEIGHT | BASE WIDTH | BASE DEPTH | APPROX. WEIGHT lbs | ı |
|-------|------|----------------|-------------------------------|---------------|---------------|--------------------------|---|
| 5804 | 4' | 45" | 23" | 18" | 30" | 12 | |
| 5805 | 5' | 57" | 34" | 20" | 35" | 15 | |
| 5806 | 6' | 68" | 45" | 21" | 44" | 18 | |