



Main

Product	Single Throw Safety Switch
Disconnect Type	Non-fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

Complementary

Line Rated Current	60 A
Device Application	Air compressor Heating ventilation and air conditioning
Mounting Type	Surface
Voltage Rating	600 V AC
Motor power hp	10 Hp at 240 V AC 50-60 Hz 25 Hp at 480 V AC 50-60 Hz 30 hp at 600 V AC 50-60 Hz
Wire Size	AWG 14...AWG 3 copper or aluminium
Height	8.74 in (222 mm)
Width	4.49 in (114 mm)
Depth	3.27 in (83 mm)

Environment

Certifications	CSA[RETURN]UL
Enclosure Rating	NEMA 3R Stainless Steel

Ordering and shipping details

Category	11931-MISCELLANEOUS ITEMS
Discount Schedule	NET
GTIN	785901595359
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.31 in (8.4 cm)
Package 1 Width	4.61 in (11.7 cm)
Package 1 Length	9.41 in (23.9 cm)
Package 1 Weight	4.06 lb(US) (1.84 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations