

Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
18 mm - Nonembeddable, Ext. Barrel Length eurofast® Connection 	Ni 8-M18E-AD4X-H1141	T4411210		8	2-Wire DC
	Ni14-M18E-AD4X-H1141	T4417292	Ext. Range	14	
	Ni10-M18E-AN6X-H1141	T4614894		10	3-Wire DC NPN
	Ni14-EM18HE-AN6X-H1141/S1589	T4611494	weldguard	14	
	Ni14-M18E-AN6X-H1141	T4611483	Ext. Range	14	
	Ni 8-M18E-AP6X-H1141	T4614794		8	3-Wire DC PNP
	Ni10-M18E-AP6X-H1141	T4641294		10	
	Ni12U-M18E-AP6X-H1141	M1645143	Uprox	12	
	Ni14-EM18HE-AP6X-H1141/S1589	T4611495	weldguard	14	
	Ni14-M18E-AP6X-H1141	T4611489	Ext. Range	14	
Ni 8-M18E-VN4X-H1141	T1571990		Comp. Output	8	4-Wire DC NPN
Ni 8-M18E-VP4X-H1141	T1561990		Comp. Output	8	4-Wire DC PNP
18 mm - Nonembeddable, Ext. Barrel Length eurofast Connection, Teflon Coated 	Ni14-MT18HE-AN6X-H1141/S1589	T4611496	weldguard	14	3-Wire DC NPN
	Ni14-MT18HE-AP6X-H1141/S1589	T4611497	weldguard	14	3-Wire DC PNP
18 mm - Embeddable, eurofast® Connection 	Bi 5-G18KK-AP6-H1141	M4670410	Short Barrel	5	3-Wire DC PNP

For detailed sensor specifications see Section M.
 Normally Closed versions available upon request, consult factory.