



## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCKD XCMD XCKT XCKP
Associated body	ZCP27 ZCP39 ZCMD21C12 ZCD31 ZCT25G11 ZCMD61M12 ZCD29 ZCT26N12 ZCMD41L2 ZCT21P16 ZCP28 ZCD35 ZCMD81L1 ZCT28P16 ZCP21M12 ZCP35 ZCMD25L2 ZCT25P16 ZCMD41L5 ZCD21M12 ZCMD21L08R12 ZCD26 ZCMD21L08U78 ZCT26P16 ZCT21N12 ZCMD39L5

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCMD41L1  
 ZCP29M12  
 ZCMD21M12  
 ZCMD21L2  
 ZCT28G11  
 ZCD39  
 ZCT21G11  
 ZCMD29L1  
 ZCMD39L1  
 ZCMD39L2  
 ZCMD29C12  
 ZCMD21L1  
 ZCD28  
 ZCP31  
 ZCP26  
 ZCMD81L5  
 ZCMD25L5  
 ZCMD29L2  
 ZCMD37L5  
 ZCD27  
 ZCT25N12  
 ZCMD21L5  
 ZCT27N12  
 ZCP29  
 ZCP37  
 ZCD37  
 ZCP25  
 ZCMD29L5  
 ZCMD69C12  
 ZCMD61C12  
 ZCT27P16  
 ZCD25  
 ZCMD25L1  
 ZCMD81L2  
 ZCT28N12  
 ZCT27G11  
 ZCD21  
 ZCD29M12  
 ZCP21  
 ZCMD37L1  
 ZCT26G11  
 ZCMD37L2

Movement of operating head	Linear
Type of operator	Side roller plunger spring return metal with vertical roller)
Type of approach	Vertical approach, 2 directions

### Complementary

Switch actuation	By 30° cam
Positive opening	Without

### Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

### Packing Units

Package 1 Weight	0.13 lb(US) (0.057 kg)
Package 1 Height	0.170 dm
Package 1 width	0.500 dm
Package 1 Length	0.320 dm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------