



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

General

| | |
|-------------------------------------|---|
| Provided equipment | Dust filter Integrated network management Rack mounting hardware Rack Mounting brackets Temperature Probe Web/SNMP Management Card |
| Number of tare power | 47 W |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |
| UPS size | WS |

Physical

| | |
|---------------------|----------------------|
| Depth | 10.24 in (26 cm) |
| Height | 3.46 in (8.8 cm) |
| Mounting preference | No preference |
| Product Weight | 22.05 lb(US) (10 kg) |
| Mounting Mode | Rack-mounted |
| Two post mountable | 0 |
| USB compatible | No |
| Width | 17.01 in (43.2 cm) |

Input

| | |
|---------------------------------|--|
| Input Frequency | 40 - 70 Hz auto-sensing |
| Number of input connectors | 1 Hard Wire 3-wire (1PH+N+G) |
| Efficiency at full load | 85...155 V |
| Maximum Input Current per Phase | 21 A |
| Switching current capacity | 30 A |
| Number of cables | 1 |
| Nominal Input Voltage | 120 V |
| Load power factor | From 0.7 leading to 0.7 lagging without any derating |

Output

| | |
|----------------------------------|--|
| Kw Rating | 1300 W |
| Max Configurable Power (Watts) | 1300 W |
| Output Frequency (sync to mains) | 50/60 Hz +/- 3 Hz sync to mains |
| Crest factor | 3 : 1 |
| Topology | Double Conversion Online |
| Waveform Type | Sine wave |
| Output connector type | Hard Wire 3-wire (H N + E) 1 |
| Bypass type | Internal Bypass (Automatic and Manual) |
| Efficiency at full load | 88 % in battery operation) |
| Graph display | 1 |
| Output voltage | 120 V |
| Maximum configurable power in VA | 1300 VA |
| Rated power in VA | 1300 VA |

Conformance

| | |
|------------------------|---------|
| Product Certifications | CSA |
| Standards | UL 1778 |

Environmental

| | |
|---------------------------------------|----------------------------------|
| Ambient Air Temperature for Operation | -40...165 °F (-40...74 °C) |
| Relative Humidity | 0...95 % non-condensing |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -40...185 °F (-40...85 °C) |
| Storage Relative Humidity | 0...95 % Non-condensing |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |
| Acoustic level | 55 dBA |
| Show note OP temperature | No |
| IP degree of protection | IP20 |

Batteries & Runtime

| | |
|--------------------------|-------------------------|
| Battery Type | External battery system |
| Included Battery Modules | 0 |
| Battery Slots Empty | 0 |
| Liquid Electrolyte Value | 0 |
| Battery Voltage | 48V |
| Battery curve | D |
| Battery power in VAH | 0 VAh runtime |
| Extendable Run Time | 0 |

Communications & Management

| | |
|---------------|--|
| Free slots | 0 |
| Control panel | Multi-function LCD status and control console |
| Audible Alarm | Audible and visible alarms prioritized by severity |

Surge Protection and Filtering

| | |
|----------------------------|-------|
| Surge energy rating | 432 J |
| Let Through Voltage Rating | 40 V |

Ordering and shipping details

| | |
|---------------------|----------------------|
| GTIN | 00731304341352 |
| Package weight(Lbs) | 26.46 lb(US) (12 kg) |

Packing Units

| | |
|------------------|--------------------|
| Package 1 Height | 7.32 in (18.6 cm) |
| Package 1 width | 21.06 in (53.5 cm) |
| Package 1 Length | 14.57 in (37 cm) |

Offer Sustainability

| | |
|-------------------|--|
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
|-------------------|--|

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 3 years repair or replace |
|----------|---------------------------|