



**ZCK E66**

**Main**

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJD39H29 ZCKJ41 ZCKJ11H29 ZCKJ41H29 ZCKJ6 ZCKJ1H7 ZCKJ5H7 ZCKJ5 ZCKJ6H29 ZCKJD35H7 ZCKJ8H29 ZCKJ21H7 ZCKJD39 ZCKJ21 ZCKJ4 ZCKJ9H7 ZCKJD31H29 ZCKJD37H29 ZCKJ1 ZCKJ21H29 ZCKJ1H29 ZCKJ2 ZCKJD37 ZCKJ4H29 ZCKJD35 ZCKJD39H7 ZCKJ5H29 ZCKJD31H7 ZCKJ2H7 ZCKJD37H7 ZCKJD35H29 ZCKJ7 ZCKJ7H29 ZCKJ8 ZCKJ2H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCKJ8H7  
ZCKJ4H7  
ZCKJ7H7  
ZCKJ6H7  
ZCKJ41H7  
ZCKJD31  
ZCKJ9  
ZCKJ9H29  
ZCKJ11H7  
ZCKJ11

Movement of operating head	Linear
Type of operator	End plunger spring return metal ball bearing mounted)
Type of approach	Multi-directional approach

### Complementary

Switch actuation	By 30° cam
Positive opening	With
Net weight	0.33 lb(US) (0.15 kg)
Head material	Metal

### Environment

Ambient air temperature for operation	50...248 °F (10...120 °C)
Ambient air temperature for storage	50...248 °F (10...120 °C)
Environmental characteristic	High temperature

### Packing Units

Package 1 Weight	0.33 lb(US) (0.150 kg)
Package 1 Height	0.041 dm
Package 1 width	0.045 dm
Package 1 Length	0.085 dm

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------