

XUX9ARCNT16

photoelectric sensor - polarised reflex - Sn 11
m - NC + NO - Pg 16



Main

Range of product	OsiSense XU
Series name	Optimum
Specific application of photoelectric detector	Object
Sensor name	XUX
Sensor design	Compact
Material	Plastic
Detection system	Polarised reflex
Emission	Red polarised reflex
[Sn] nominal sensing distance	11 m polarised reflex
Wiring technique	5 wires
Type of output signal	Discrete
Discrete output function	1 NO + 1 NC
Add on output	Without
Electrical connection	Screw-clamp terminals 1 x 1.5 mm ² or 1 x 0.75 mm ² with adaptor
[Us] rated supply voltage	24...240 V AC/DC
Switching capacity in mA	0,5 A cos ϕ = 0.4 for 0.5 million cycles at 1 operating cycle per second at 250 V 3 A cos ϕ = 1 for 0.5 million cycles at 1 operating cycle per second at 250 V

Complementary

Electronic sensor type	Photo-electric sensor
Enclosure material	PBT
Lens material	PMMA
Maximum sensing distance	15 m polarised reflex
Output type	Relay
Cable entry	1 entry for M16 x 1.5 cable gland 7...10 mm
Status LED	1 LED yellow output state 1 LED green supply
Supply circuit type	AC/DC
Supply voltage limits	20...264 V AC/DC
Switching frequency	$\leq$ 20 Hz
Voltage drop	$\leq$ 1,5 V closed state
Power consumption in W	2 W AC/DC
Delay first up	< 60 ms
Delay response	< 25 ms
Delay recovery	< 25 ms
Setting-up	Sensitivity adjustment
Electrical durability	500000 cycles 1 3000 cyc/mn relay 500000 cycles 0,4 500 cyc/mn relay
Depth	30 mm
Height	92 mm
Width	77 mm
Product weight	0,2 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	CE CSA UL
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C
Vibration resistance	7 gn +/- 1.5 mm 10...55 Hz IEC 60068-2-6
Shock resistance	30 gn 11 ms IEC 60068-2-27
IP degree of protection	IP65 double insulation IEC 60529 IP67 double insulation IEC 60529
RoHS EUR conformity date	0914
RoHS EUR status	Compliant