

# Product data sheet

## Characteristics

# PHG36030GN

Plug-in unit, I-Line Busway, H-frame, 30A, 3 phase, 4 wire, 600VAC, 18kA, ground, neutral



### Main

Range of Product	I-Line
Product or Component Type	Plug-in unit
Module type	H-Frame

### Complementary

[Ue] rated operational voltage	600 V AC 50/60 Hz 277/480 V AC 50/60 Hz
Phase	3 phase
Busbar description	Ground
Fuse type	H
Breaking capacity code	G
Disconnecter device type	Thermal magnetic circuit breaker 30 A 18 kA 600 V Thermal magnetic circuit breaker 30 A 35 kA 480 V Thermal magnetic circuit breaker 30 A 65 kA 240 V
Level or class	Class 5600
Wiring configuration	4-wire

### Environment

Product Certifications	UL[RETURN]CSA
------------------------	---------------

### Ordering and shipping details

Category	20183-PFH /PHG/PHJ/ PHL C/B PLUGS
Discount Schedule	PE7
Returnability	No
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	32.00 lb(US) (14.515 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------