




**Catalog Number:** LTGCS07B-B  
**Product ID:** 7TAA012LH0R0006  
**UPC Number:** 78621010754  
**EAN Number:** 05415022390995  
**Status:** A



Liquid Tight Flexible Metallic Conduit, General Purpose, Galvanized Steel Core with PVC Jacket, Conduit Size 2 Inch, Length 15 Meters/50 Feet, Working Temperature -40 to 75 Degrees C, CSA heavy duty LR-72635, Compliant to RoHS, Black

General Purpose, CSA Certified Liquid-tight Flexible Metallic Conduits provide excellent strength and liquid-tight performance, meeting CEC requirements

Representative

- Full compliance to IEC 61386 requirements, CE compliant
- Coordinated performance with Ser. 52/53 Steel Fittings
- CSA & IP ingress protection ratings aligned with industrial enclosures
- Smooth extruded jackets provide best performance with fittings
- Conduit sizes 1/2" and up meets CSA Heavy duty requirements, when used with series 5200/5300 liquid-tight fittings
- Ideal for machine and equipment, OEMs, panel builders and industrial, light manufacturing, commercial and outdoor installations
- Liquid tight applications against water, oils, cutting fluids, mild acids
- For use in electrical circuits up to 1,000 volts

#### North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Type	Liquid Tight Flexible Metallic Conduit
Special Features	Designed to meet CSA C22.2 No. 56 ID/OD dimension requirements
Application	For use to CEC as described in Section 12-1300 for dry damp or wet locations where flexibility is required
Standard	CSA, RoHS
Trade Size	2 in
Outside Diameter	2.375 in
Inside Diameter	2.020 in
Length	50 ft ; 15 m
Radius	279 mm
Material	Galvanised Steel
Finish	PVC Jacket
Color	Black

#### European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	63mm
Nominal size in inch	2 inch
Outer diameter	60.33mm
Inner diameter	51.31mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	PVC
Operating temperature	-40-+75°C
Degree of protection (IP)	IP67
Weight	2.16kg/m



Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23	Y
With approval according to UL	N
Approved according to CSA	Y

#### **Packaging**

Outer Quantity	50
Outer Dimensions (inches)	33.62x37x10.38
Weight Uom	1.54 lbs. Each

#### **Documents / Support Tools**

Technical Drawing / Data Sheet	TDS000003
Technical Drawing / Data Sheet	TDS000117
Catalog Page	Available on Website
Support/Tools	Available on Website
Support/Tools Canada	Available on Website

**For further technical assistance, please contact us...**

ABB Installation Products Canada  
700, Thomas Avenue  
Saint-Jean-sur-Richelieu, QC  
J2X 2M9  
[www.tnb.ca](http://www.tnb.ca)

ABB Installation Products Technical Support  
<http://www.tnb.ca/en/contactus/?id=ALL>

Hours: 7h00 - 18h00  
Monday-Friday