


NON INSULATED FERRULES DIN 46228/1



Technical Information
Material: E-Copper,
Surface electro tinned.
Minimum Coating Thickness 3µm.
Rated at 600V Max
Tolerances: after part 1



Non-Insulated Ferrules

Rated at 600V

Part-No.	AWG	Size mm ²	d1	d2	l	s	Packing Unit	Approved Tool V Series	CRIMP TOOLS		
									RAT-FER	SPR-FER	RAT-FER2
FERN-20-10M	20	0,75	1,20	2,30	10,00	0,15	1	V915	●		
FERN-18-10M	18	1,00	1,40	2,50	10,00	0,15	1	V915	●		
FERN-16-10M	16	1,50	1,70	2,80	10,00	0,15	1	V915	●		
FERN-14-10M	14	2,50	2,20	3,40	10,00	0,15	1	V915	●		
FERN-12-12M	12	4,00	2,80	4,00	12,00	0,20	1	V915	●		
FERN-10-12B	10	6,00	3,50	4,70	10,00	0,20	250	V915	●		
FERN-8-12B	10	6,00	3,50	4,70	12,00	0,20	250	V915	●		
FERN-6-12B	8	10,00	4,50	5,80	12,00	0,20	250	V915		●	
FERN-20-10M	6	16,00	5,80	7,50	12,00	0,20	250	V915		●	
FERN-4-12B	4	25,00	7,30	9,50	12,00	0,20	250	V915		●	
FERN-2-12C	2	35,00	8,30	11,00	12,00	0,20	100	V915		●	
FERN-1/0-18C	1/0	50,00	10,30	13,00	18,00	0,30	100	V925		●	
FERN-2/0-25C	2/0	70,00	12,50	15,00	25,00	0,40	100	V925		●	
FERN-3/0-25L	3/0	95,00	14,50	17,00	25,00	0,40	50	V940			●
FERN-4/0-32L	4/0	120,00	16,50	19,00	32,00	0,50	50	V940			●

For Copper Stranded Wire Only

See Page E-2 for tools.

INSULATED FERRULES IN CUT-STRIP FORM

Technical Information
Insertion Funnel is made of Polypropylene
and is heatresistant up to 105 Deg. C.
Material: E-Copper,
Surface electro tinned.
Minimum Coating Thickness 3µm.
Rated at 600V Max
Tolerances: after part 4



Cut-Strips Polypropylene Insulated Ferrules

Rated at 600V Max, 105°C

Colour DIN	Part-No.	AWG	Size mm ²	d1	d2	l1	l2	s1	s2	a1	a2	a3	a4	Packing Unit	Approved Tool
	FERSTR-22WH	22	0,50	1,00	2,60	14,00	8,00	0,15	0,30	0,20	3,60	0,25	1,50	500(10x50)	SPR-JOK
	FERSTR-20GR	20	0,75	1,20	2,80	14,00	8,00	0,15	0,30	0,20	3,60	0,25	1,50	500(10x50)	SPR-JOK
	FERSTR-18RD	18	1,00	1,40	3,00	14,00	8,00	0,15	0,30	0,20	4,20	0,25	1,50	500(10x50)	SPR-JOK
	FERSTR-16BK	16	1,50	1,70	3,50	14,00	8,00	0,15	0,30	0,20	4,20	0,25	1,50	500(10x50)	SPR-JOK
	FERSTR-14BL	14	2,50	2,20	4,20	14,00	8,00	0,15	0,30	0,20	5,00	0,25	1,50	500(10x50)	SPR-JOK

For Copper Stranded Wire Only

See Page E-5 for tools.

