



## Main

Range	Thalassa
Accessory / separate part category	Fixing accessory
Product or Component Type	Wall fixing support
Device Application	Multi-purpose
Enclosure nominal dimensions	-
Mounting Location	Top and bottom, on rear of the enclosure
Range compatibility	Thalassa Thalassa PLM
Device composition	Fixing screws 4 lug

## Complementary

Material	Polyamide 6 with 30 % fibre glass
Color	Gray RAL 7035)
Fixing mode	Screwed - from the outside
Permanent permissible load	220.46 Lb(US) (100 kg) horizontal position 440.92 lb(US) (200 kg) vertical position
Height	12.13 ln (308 mm) 16.93 ln (430 mm) 20.87 ln (530 mm) 25.47 ln (647 mm) 29.41 ln (747 mm) 33.35 ln (847 mm) 41.57 in (1056 mm)
Width	10.04 ln (255 mm) 12.99 ln (330 mm) 16.93 ln (430 mm) 17.17 ln (436 mm) 21.10 ln (536 mm) 25.04 ln (636 mm) 33.54 in (852 mm)

## Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480774331
Returnability	Yes
Country of origin	ES

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.18 in (3.000 cm)
Package 1 Width	3.94 in (10.000 cm)
Package 1 Length	5.31 in (13.500 cm)
Package 1 Weight	7.88 oz (223.300 g)
Unit Type of Package 2	S04
Number of Units in Package 2	75
Package 2 Height	11.81 in (30.000 cm)

Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	38.15 lb(US) (17.304 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	300
Package 3 Height	17.72 in (45.000 cm)
Package 3 Width	31.50 in (80.000 cm)
Package 3 Length	47.24 in (120.000 cm)
Package 3 Weight	179.05 lb(US) (81.216 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations