

# Product Datasheet

## Characteristic

# XCMD2102L5

limit switch XCMD - steel roller plunger -  
1NC+1NO - snap - 5 m



## Main

range of product	OsiSense XC
series name	standard format
product or component type	limit switch
device short name	XCMD
sensor design	miniature
body type	fixed
head type	plunger head
material	metal
body material	zamak
head material	zamak
fixing mode	by the body
movement of operating head	linear
type of operator	spring return roller plunger metal
type of approach	lateral approach 2 directions
number of poles	2
contacts type and composition	1 NC + 1 NO
contacts operation	snap action

## Complementary

switch actuation	by 30° cam
electrical connection	removable cable connector
cable length	5 m
cable composition	5 x 0.75 mm <sup>2</sup>
wire insulation material	PvR
contacts insulation form	Zb
positive opening	with
positive opening minimum force	35 N
minimum force for tripping	7 N
maximum actuation speed	1.64 ft/s (0.5 m/s)
contact code designation	B300, AC-15 (Ue = 240 V, Ie = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A

	R300, DC-13 (Ue = 250 V, Ie = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A
[Ui] rated insulation voltage	300 V degree of pollution 3 conforming to UL 508 400 V degree of pollution 3 conforming to IEC 60947-5-1 300 V degree of pollution 3 conforming to CSA C22.2 No 14
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60664 4 kV conforming to IEC 60947-1
short circuit protection	6 A by gG cartridge fuse
electrical durability	5000000 cycles, DC-13, 120 V, 1 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13, 24 V, 3 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13, 48 V, 2 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
mechanical durability	10000000 cycles
width	1.18 in (30 mm)
height	1.97 in (50 mm)
depth	0.63 in (16 mm)

## Environment

shock resistance	25 gn (duration = 18 ms) conforming to IEC 60068-2-27
vibration resistance	5 gn (f = 10...500 Hz) conforming to IEC 60068-2-6
IP degree of protection	IP66 conforming to IEC 60529 IP67 conforming to IEC 60529 IP68 conforming to IEC 60529
IK degree of protection	IK06 conforming to EN 50102
overvoltage category	class I
ambient air temperature for operation	-13...158 °F (-25...70 °C)
product certifications	CSA UL
standards	EN 60947-5-1 IEC 60947-5-1 UL 508 CSA C22.2 No 14

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1002 -
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------