




P.V.C. Plastic Insulated Sleeve


8 WIRE RANGE

.050 Stock

Stud Size		Part Number
8-10		761603
12-1/4		761600
1/4-5/16		761602
5/16-3/8		761601
7/16-1/2		761604

Terminals & Splices accept .385" Max. Wire Ins. Dia.




600 Volt Rated 105°C Temperature Rating



DIMENSIONAL CHART		
Part Number	W	L
761603	0.603"	1.421"
761600	0.603"	1.421"
761602	0.603"	1.421"
761601	0.603"	1.421"
761604	0.825"	1.718"


6 WIRE RANGE

.057 Stock

Stud Size		Part Number
8-10		761605
12-1/4		761610
1/4-5/16		761612
5/16-3/8		761611
7/16-1/2		761023

Terminals & Splices accept .440" Max. Wire Ins. Dia.

600 Volt Rated 105°C Temperature Rating



DIMENSIONAL CHART		
Part Number	W	L
761605	0.645"	1.673"
761610	0.645"	1.673"
761612	0.645"	1.673"
761611	0.645"	1.673"
761023	0.837"	1.861"



Copper Stranded Wire Only

Approved installation tool: 640013900
Economy installation tool: LUG-8-2-INS
See pages E-2 to E-5 for installation tools.



LISTED