LX9FG415

TeSys F - specific contactor coil - 415...440V AC 40...400 Hz low consumption





Main

Range	TeSys
Product or Component Type	Specific contactor coil
Device short name	LX9FG
Range compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F185 LC1F225
Control circuit type	AC 40400 Hz low consumption
[Uc] control circuit voltage	415440 V AC 40400 Hz
Inductance of closed circuit	20.6 H
Average resistance	157 Ohm inrush 68 °F (20 °C) 5930 Ohm holding 68 °F (20 °C)
Operating time	130 ms opening 35 ms closing
Mechanical durability	10 Mcycles
Maximum operating rate	2400 cyc/h 131 °F (55 °C)

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Operational 0.851.1 Uc 131 °F (55 °C)) Drop-out 0.20.55 Uc 131 °F (55 °C))	
Inrush power in VA	9501180 VA 40400 Hz (at 68 °F (20 °C))	
Hold-in power consumption in VA	8.910.9 VA 40400 Hz (at 68 °F (20 °C))	
Heat dissipation	89.8 W	

Environment

Ambient Air Temperature for Operation	23131 °F (-555 °C)
Net Weight	1.21 lb(US) (0.55 kg)

Ordering and shipping details

0 11 0		
Category	22341-CONTACTOR,D,K,&F ACCESS	
Discount Schedule	l12	
GTIN	3389110084054	
Returnability	No	
Country of origin	CZ	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.95 in (7.500 cm)	
Package 1 Width	4.13 in (10.500 cm)	
Package 1 Length	7.01 in (17.800 cm)	
Package 1 Weight	20.14 oz (570.900 g)	
Unit Type of Package 2	S03	
Number of Units in Package 2	14	

Package 2 Height	11.81 in (30.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	18.62 lb(US) (8.444 kg)	

Offer Sustainability

Green Premium product
☑ REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
☐ China RoHS Declaration
€Yes
Product Environmental Profile
[™] End Of Life Information

Contractual warranty

Warranty	18 months