# SSP04EMA48D

Surge protection device, Surgelogic, EMA, 480kA, 480Y/277VAC, 3 phase, 4 wire, NEMA 1, disconnect switch



#### Main

Product	Surge protection device
Range	Surgelogic
Device Short Name	EMA

## Complementary

Complementary		
Voltage Rating	480Y/277 V AC	
MCOV	320 V	
SCCR	200 kA	
Surge Current	480 kA	
Nominal Discharge Current	20 kA	
Rated Current	150 A	
Number of Phases	3 phase	
Max Number of Poles	3	
Wiring Configuration	4-wire	
Connection	Lugs AWG 10AWG 3/0 copper 35.40 lbf.in (4 N.m)	
Local Signalling	Status LED green per phase normal operation Status LED red per phase fault	
Provided Equipment	Alarm enable/disable switch Switch-disconnector Surge counter Dry contacts	
Cable length	19.02 in (483 mm)	
Device Mounting	Surface	
Height	21.61 in (549 mm)	
Width	9.88 in (251 mm)	
Depth	7.87 in (200 mm)	

#### **Environment**

Ambient Operating	149 °F (65 °C)	
Enclosure Rating	NEMA 1	
Enclosure Material	Gray painted sheet steel	
Standards	CSA C22.2 No 8 UL 1449:ed. 4 UL 1283:ed. 5	

## Ordering and shipping details

Category	08464-SURGE PROTECTION EMA
Discount Schedule	DE1B
GTIN	785901077275
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	21.61 in (54.9 cm)	
Package 1 Width	9.88 in (25.1 cm)	
Package 1 Length	7.87 in (20.0 cm)	
Package 1 Weight	20.50 lb(US) (9.299 kg)	

### Offer Sustainability

REACh Declaration
Compliant with Exemptions
China RoHS Declaration
₫ Ves