


TYPE ILSCONS

Features

- Color coded
- Funnel Entry
- Manufactured from high strength copper alloy
- Electro-tin plated
- Vinyl insulation
- Packaged in convenient small quantities
- UL Listed and CSA Certified for 600 volts, 90° C

Benefits

- Provides easy wire range identification
#22-16 AWG Red
#16-14 AWG Blue
#12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Attractive resealable packaging designed for merchandise racks
- Ensures reliability for copper conductor



Catalog Number	Wire Range	Stud Size	Dimensions		Maximum Wire Insulated Diameter	Connector Type
			L	W		
44201-B100	16-22	6	.764	.26	.145	Vinyl Insulated Ring Terminals (Expanded)
44201-B1000	16-22	6	.764	.26	.145	Vinyl Insulated Ring Terminals (Expanded)
44203-B100	18-22	10	.819	.315	.145	Vinyl Insulated Ring Terminals (Expanded)
44203-B1000	18-22	10	.819	.315	.145	Vinyl Insulated Ring Terminals (Expanded)
44211-B100	14-16	6	.764	.26	.175	Vinyl Insulated Ring Terminals (Expanded)
44211-B1000	14-16	6	.764	.26	.175	Vinyl Insulated Ring Terminals (Expanded)
44213-B100	14-16	10	.858	.335	.175	Vinyl Insulated Ring Terminals (Expanded)
44213-B1000	14-16	10	.858	.335	.175	Vinyl Insulated Ring Terminals (Expanded)
44214-B100	14-16	1/4	1.055	.472	.175	Vinyl Insulated Ring Terminals (Expanded)
44214-B1000	14-16	1/4	1.055	.472	.175	Vinyl Insulated Ring Terminals (Expanded)
44222-B50	10-12	10	1.047	.374	.255	Vinyl Insulated Ring Terminals (Expanded)
44222-B500	10-12	10	1.047	.374	.255	Vinyl Insulated Ring Terminals (Expanded)
44223-B50	10-12	1/4	1.167	.472	.255	Vinyl Insulated Ring Terminals (Expanded)
44223-B500	10-12	1/4	1.167	.472	.255	Vinyl Insulated Ring Terminals (Expanded)
44224-B50	10-12	3/8	1.339	.591	.255	Vinyl Insulated Ring Terminals (Expanded)
44224-B500	10-12	3/8	1.339	.591	.255	Vinyl Insulated Ring Terminals (Expanded)

Can be supplied in bulk. Consult factory for part number.

Other sizes available on request. Contact factory for pricing.